

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 700340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 24; & 19, T21-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 551)

Set post 4" dia., 4 ft. long, with marked stone 12" in ground for qr. sec.cor. marked $\frac{1}{4}$ S on W. face; from which
A Fir 30" dia., bears N.45°W., 29 lks. dist. mkd. $\frac{1}{4}$ S BT.
A Fir 30" dia., bears N.68°E., 14 lks. dist. mkd. $\frac{1}{4}$ S BT.

Wilford N. Haines, #239 - Filed Feb. 17, 1960 - C.S. File 51/67-2

Set 1" x 1" x 36" T. Iron from which scribed
12" Fir, N.50°E., 18.6 ft.
40" Fir, N.17°E., 41.1 ft.

BLM resurvey by Wayne L. Rogers and Dale T. Bedell, Cadastral Surveyors, under Group #1392, surveyed Aug/Nov. 1987 - (DCSO records Vol. 48 Page(s) 18467)

The $\frac{1}{4}$ sec. cor., reestablished by proportionate measurement and recorded by Haines in 1960, there is no remaining evidence of the original corner, therefore this position is accepted as the corner; monumented with a "T" shaped iron rod, 1" dia., firmly set, projecting 4" above ground, with washer mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE, from which the bearing trees mkd. by Haines:

A Fir 52" dia., bears N.17°E., 62 lks. dist., with scribe marks $\frac{1}{4}$ S BT visible on the bark.
A Fir 22" dia., bears S.50°E., 28 lks. dist. with healed blaze.

At the corner point

Set an stainless steel post, 28" long, 2 1/2" dia., 22" in the ground, directly over the iron rod, with brass cap mkd:

T 21 S
R 7 W R 6 W
 $\frac{1}{4}$
S 24 | S 19
1987

from which a new bearing tree

A Fir 16" dia., bears S.81°W., 10 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S24 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.