

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24; 18 & 19, T21-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 551)

Set post 6" dia., 4 ft. long, in ground 24"; raised mound of rocks alongside, for cor. to secs. 18, 19, 13 and 24, marked T21S S18 on NE.; R6W S19 on SE.; R7W S24 on SW.; S13 on NW. face, with 3 notches on S. and 3 on N. face; from which
A Fir 30" dia., bears N.13°E., 56 lks. dist. mkd. T21S R6W S18 BT.
A Fir 24" dia., bears S.23°E., 75 lks. dist. mkd. T21S R6W S19 BT.
A Stub 30" dia., bears S.20°W., 80 lks. dist. mkd. T21S R7W S24 BT.
Mound of rocks bears N.50°W., 25 lks. dist.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon Tracy; C. Putnam - Dec. 1961 - C.S. File 49/89-6

Found - Old mound of rock at corner.
Fir tree, now 40", N.13°E., 30.0 ft., not 37.0 ft. Traces of old bark scribing visible "1 S", legible. Tree in good condition.
Fir tree, uprooted and down, S.23°E., 49.5 ft. dist., not checked, shows good scars. Did not open.
Mound of rock, N.50°W., 25 lks. not found, area shows evidence of slide.
Stub of SW. not found.

Set Brass cap at cor. mkd: County Surveyors Office

T 21 S
S 13 | S 18
S 24 | S 19
R 7 W R 6 W
1961

New BTs- 18" Fir S.27°E., 28.5 ft. mkd: T21S R7W S19 CS BT
30" Fir S.84°W., 59.4 ft. mkd: T21S R7W S24 CS BT (1 blaze)
24" Fir S.27°W., 58.0 ft. mkd: T21S R7W (in bark) S24 CS BT (in wood)
Cor. is on very steep slope (45°) on top of vertical rock bluff 20 ft. high.

Fd. OK, and used in BLM Resurvey by Wayne Rogers & Joel Robb, Cadastral Surveyors, Group #1318, Surveyed May/Nov. 1986 - (DCSO records Vol. 48 Page(s) 18312)

(Cont. Next Page)

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24; 18 & 19, T21-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by Wayne L. Rogers and Dale T. Bedell, Cadastral Surveyors, under Group #1392, surveyed Aug/Nov. 1987 - (DCSO records Vol. 48 Page(s) 18467-68)

The sec. cor., perpetuated and recorded by Godfrey in 1961, monumented with an iron post 1½" dia., firmly set, projecting 15" above ground, with brass cap as mkd. in 1961, from which an original bearing tree

A Fir 45" dia., bears N.13°E., 45 lks. dist., with fragmentary scribe marks.

and the remains of bearing trees mkd. by Godfrey:

A split Fir snag, size indeterminate bears S.25½°E., 43 lks. dist., with healed blaze.

A Fir 29" dia., bears S.29½°W., 87 lks. dist., with healed blaze.

A Fir 38" dia., bears S.85 3/4°W., 90 lks. dist. with healed blaze.

The corner is on a rock bluff, facing S.