

PRIMARY CORNER DESCRIPTION WC Sec. Cor. for 12 & 13; 7 & 18, T21-6

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 552)

-----  
 A Vine Maple 6" dia. for cor. to secs. 12, 13, 7 and 18, marked T21S S7 on NE.; R6W S18 on SE.; R7W S13 on SW.; S12 on NW. face, with 4 notches on S. and 2 on N. edge, from which  
 Fir 20" dia., bears N.20°W., 64 lks. mkd. T21S R7W S12 BT.  
 Fir 20" dia., bears N.75°E., 70 lks. mkd. T21S R6W S7 BT.  
 Fir 24" dia., bears S.53°E., 43 lks. mkd. T21S R6W S18 BT.  
 Fir 20" dia., bears S.58°W., 44 lks. mkd. T21S R7W S13 BT.

Wilford N. Haines, #239 - For: Harold Woolley - Dec. 18, 1957 M 8-7 and (Haines field book, H-68)

-----  
 Found Fir bT, N.20°W., 42.24 ft.  
 Set Lot Marker (in creek), from which scribed:  
 40" Fir S.45°W., 23.3 ft.  
 30" Fir N.45°E., 57.5 ft.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy and crew - March 3, 1964 - C.S. File 49/143-24

-----  
 Found - Haines "T" Iron at cor. in creek bed.  
 30" Fir N.45°E., 57.5 ft., Haines scribing visible. Tree standing and alive.  
 Orig. BT, 20" Fir N.20°W., 42.2 ft. uprooted and down, old blaze previously opened, scribing visible on old face, "BT S12 T21 R7W".  
 Haines SW. BT, 40" Fir, S.45°W., 23.3 ft., also uprooted and down.

Set WIT. COR. 23 ft. East of corner. (Sec. line runs right in creek bed) Set Brass cap at cor. mkd: County Surveyors Office

T 21 S  
 W.C. 23' W. to corner  

S 12	S 7
S 13	S 18
R7W	R6W

 1964

from which  
 Haines NE. BT to sec. cor., 30" Fir, bark scribed, bears N.20°E., 45.5 ft. from Wit. Corner, not rescribed.  
 New BTs- 9" Hemlock N.14°W., 75.0 ft. "T21S R7W S12 CS BT.  
 Wit. Cor. in W. edge of logging road.  
 36" Red Cedar S.22°W., 125.6 ft. mkd: "T21SR7W S13 CS BT"

continued next page

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION WC Sec. Cor. for 12 & 13; 7 & 18, T21-6

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Ronald L. Rice, Ward NW - For: Seneca Jones Timber Co. -  
7/2006 - M 151-15

-----  
Found - 2½" DCSO brass cap dated 1964 & marked in part WC  
23' WC to corner with the following accessories:  
Haines T iron in creek bed marking true section  
corner position not found.  
30" D.Fir rotted stump bears N.20°E. 45.5', no marks  
32" Hemlock bears N.14°W., 75.0' - healed face.  
44" Red Cedar bears S.22°W., 125.6' - healed face.  
New BTs- 14" alder bears N.19°W., 8.0', bark scribed X BT.  
7" Hemlock bears S.69°E., 56.9', blazed-scribed X BT  
All BTs have red painted band & face plus BT tag.  
Galvanized post set adjacent to corner monument.

Daniel Baker - For: Seneca Jones Timber Co. - 7/2019 - C.S.  
File 65/103-11

-----  
Found - 2½" Douglas County brass cap "1964"  
16" Alder, N.16°W., 8.0' to center, M151-15 BT  
(record = N.19°W., 8.0)  
12" Hemlock, S.69°E., 56.8' to center, M151-15 BT  
(record = S.69°E., 56.9')  
44" R.Cedar, S.22°W., 125.6' to center Douglas  
County BT (record = S.22°W., 125.6')  
35" Hemlock, N.14°W., 75.0' to center - Douglas  
County BT (record = N.14°W., 75.0')