

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 700540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 12; & 7, T21-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 552)

Set post 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on W. face; from which
A Fir 12" dia., bears N.72°W., 30 lks. dist. mkd. $\frac{1}{4}$ S BT.
A Fir 48" dia., bears N.28°E., 31 lks. dist. mkd. $\frac{1}{4}$ S BT.

Wilford N. Haines, #239 - Filed Feb. 17, 1960 - C.S. File 51/67-2

Set 1" x 1" x 36" T. Iron from original BTs.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - and crew - March 3, 1964 - C.S. File 49/143-23

Found - "T" Iron set by Haines.
24" Fir, N.72°W., 19.8 ft., scribing visible on old face, previously opened " $\frac{1}{4}$ S".
Badly rotted Fir stump, N.28°E., 20.5 ft. No marks found.
New BTs- 9" D.Fir N.88°E., 18.6 ft. mkd. $\frac{1}{4}$ S7 CS BT.
7" D.Fir N.16°W., 17.4 ft. mkd. $\frac{1}{4}$ S12 CS BT.
Old NW. tree appears to be dying.

Kent Inman - For: Seneca Jones Timber Co. 10/2009 - M160-12

Found - 1" brass washer on a 1" iron T-post mkd: WILFORD N HAINES 239 SURVEY POINT DRAIN ORE (cap orientated East)
Remains of an original bearing tree, now a decaying up-rooted windfall, size indeterminate. Root hole bears N.72°W. (19.8')
29" D.Fir, with a healed face, bears N.18°W., 16.6'
25" D.Fir, with a healed face, bears N.88°E., 18.3'
New BTs- 19" D.Fir bears S.47°E., 43.6' scribed $\frac{1}{4}$ S7 BT
9" D.Fir bears S.23°W., 45.8' scribed $\frac{1}{4}$ S12 BT
Metal U fence post was placed 1' north of the monument.

Daniel Baker - For: Seneca Jones Timber Co. - 7/2019 - C.S. File 65/103-11

Found - 1" brass disk on 1"x1" - "T" iron per C.S.51/67-2
16" Fir, N.87°E., 18.3' to center Douglas County BT (Rec. N.88°E., 18.3')
20" Fir, S.46°E., 43.6' to center M160-12 BT (rec. S.47°E, 43.6') Continued next page

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 700540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 12; & 7, T21-6

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

16" Fir, S.21°W., 45.8' to center M160-12 BT (rec.
= S.23W., 45.8')
28" Fir, N.19°W., 16.6' to center Douglas County BT
(Rec. N.16°W., 17.4')
5 ft metal post alongside corner