

PRIMARY CORNER DESCRIPTION NE. Cor. Section 1 (NW cor. S. 6, T21-6)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 554)

At point of intersection (20.30 chs. East of cor. to T20S Rs. 6 & 7 W.), I set triangular post, 6" dia., 4 ft. long, 24" in ground for closing cor. to T21S R6 & 7 W., marked T20S R6W S21 on N.; R6W S6 on SE.; T21S S1 on SW. face, with 6 notches on S.; E.; and W. edges; from which
A Fir 20" dia., bears N.20°W., 19 lks mkd. T20S R6W S31 BT
A Fir 12" dia., bears S.43°W., 14 lks. mkd. T21S R7W S1 BT
A Fir 20" dia., bears S.18°E., 45 lks. mkd. T21S R6W S6 BT

Wilford Haines, #239 - For: Woolley Logging Co - 1956 - M3-23

Found all bearing trees.
Set an angle iron at point for corner.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2268, Surveyed March/July 2009 - DCSO records Vol. 57 Pages 22623-4

The original closing cor. of T21S Rs. 6 & 7 W., perpetuated by Haines, in 1956, monumented with a "T" shaped iron rod, 3/4" dia., firmly set, projecting 14" above the ground, with brass disk on top, mkd. WILFORD N HAINES RLS 239 SURVEY POINT DRAIN ORE, from which the remains of the original BTs
A sawed fir stump, 32" dia., bears S.18°E., 25.1 ft., with a healed blaze. (Record, 29.7 ft.)
A fir snag, 20" dia., bears N.20°W., 15.1 ft., with no marks visible. (Record, 12.5 ft.)
and a bearing tree of unknown origin
A fir, 7" dia., bears S.76½°W., 20.5 ft., with a healed blaze.

At the corner point
Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, directly over the "T" shaped iron rod, with brass cap mkd.

T20S R6W
S 1 | S 6
C C
T21S
R7W R6W

2009 from which
A fir, 6" dia., bears S.54¾°E., 6.3 ft., mkd. T21S R6W S6 CC BT.
A fir, 16" dia., bears S.9¼°W., 28.2 ft., mkd. X BT.
Deposit a magnet in a white plastic case at the base of the stainless steel post.