

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 100240

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 30 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 2 Page(s) 888)

A Fir 30" dia., for ¼ sec. cor. mkd. ¼ S on W. face, from which
 A Maple 6" dia., bears N.45°E., 13 lks. dist. mkd. ¼ S BT.
 A Chittem 6" dia., bears S.60°W., 20 lks. dist. mkd. ¼ S BT.

GLO Resurvey by Norman D. Price and George Rigby, Cadastral Engineers, under Group #282, Surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11381)

(37.64 chs.)
The ¼ sec.cor. of sec. 30 only, a sawed Fir stump, 38" dia., 7 ft. high, mkd. ¼ S on N. side; from which
 A Maple stool, bears N.45°E., 13 lks. dist. remains of old bearing tree.
 A Dogwood stool, bears S.60°W., 20 lks. dist., remains of old bearing tree.

(0.10 chs., N.1°03'E.)
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for witness cor. to the ¼ sec. cor. of sec. 30 only, with brass cap mkd:
 WC
 ¼ S 30
 1945

from which
 A Fir 28" dia., bears N.40°E., 183 lks. dist. mkd. W C ¼ S30 BT.
 A Fir 28" dia., bears N.80¼°E., 245 lks. dist. mkd. W C ¼ S30 BT.