

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 100276

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25 only, T21-9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Alonzo Gesner, Deputy Surveyor, under Contract #608 -dated April 17, 1893 - (DCSO records Vol. 2 Page(s) 917-18)

At an intersection point, 4.20 chs. S. of cor. to 19 & 30) Set Fir post 5 ft. long, 6" dia., 24" in the ground on hill side sloping West for closing cor. to secs. 24 and 25, marked CC T21S on the W.; R9W S25 on the S.; ans S24 on the N. faces with 2 grooves on the S. and 4 grooves on the N. sides, from which

A Fir 12" dia., bears N.80°E., 96 lks. dist. mkd. CC T21S R9W S24 and 25 BT.

A Fir 40" dia., bears N.50°W., 56 lks. dist. mkd. T21S R9W S24 BT.

A Fir 48" dia., bears S.69°W., 156 lks. dist. mkd. T21S R9W S25 BT.

GL0 Resurvey by Norman D. Price and George Rigby, Cadastral Engineers, under Group #282, Surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11381-82)

(After a careful investigation, it is developed that Gesner's recorded retracement of this line is entirely fictitious, that it is a deliberate fabrication on his part for the purpose of justifying his own work and creating a limiting boundary for T21S R9W., and is therefore rejected as a suitable basis for restoration of lost corners referring to T21S R8W.) (Vol. 27 Pg. 11379)

The closing cor. of secs. 24 and 25, the locus of which is determined by reference to the record bearing and distance from the old NE. bearing tree and record distance from the old NW. bearing tree.

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

C C	T 21 S S 24 S 25 R 9 W	T 21 S R 8 W S 30
	1945	

from which

A dead Fir 26" dia., N.80°E., 96 lks. dist. on which I uncover scribe marks CC T21S R9W S24 & S25 BT. (Old BT)

A Fir stub, badly burned 40" dia., bears N.31¼°W., 56 lks. dist., on which no marks remain. (Old BT)

A Fir 48" dia., bears N.33°W., 218 lks. dist., mkd. T21S R9W S24 CC BT. (New BT)

No other accessory available.

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 100276

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25 only, T21-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - John M. Powell, and crew - May 11, 1973 - C.S. File 56/25-21

Found - GLO brass cap C.C., properly mkd., 1945.
26" Fir stump, N.80°E., 63.4 ft.
48" Fir stump, N.33°W., 143.9 ft.
1" Iron pipe alongside of brass cap.
New BTs- 6" D.Fir N.31°W., 11.3 ft. scribed S24 CC CS BT.
8" D.Fir, South, 29.9 ft. scribed S25 CC CS BT.
Cor. lies in old clear cut very brushy. A lot of new growth.
It lies on westerly slope approx. 60 ft. westerly of ridge top.