

PRIMARY CORNER DESCRIPTION C C for Secs. 13 & 24 only, T21-9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608 -dated April 17, 1893 - (DCSO records Vol. 2 Page(s) 920 & Vol. 3 pg 921)

-----  
 (At point of intersection, 417 lks. South of cor. to secs. 18 & 19)

I set a Fir post 4½ ft. long, 4" sq., 24" in the ground on top ridge at point of intersection for C.C. to secs. 13 & 24, marked C C T21S on the W.; R9W S24 on the S.; and S13 on the N. faces, with 3 grooves on the N. and S. sides, from which  
 A Hemlock 24" dia., bears S.35°E., 21 lks. dist. mkd. CC T21S R9W S13 and 24 BT.

A Hemlock 12" dia., bears S.36°W., 89 lks. dist. mkd. T21S R9W S24 BT.

A Hemlock 10" dia., bears N.47°W., 33 lks. dist. mkd. T21S R9W S13 BT.

GLO Resurvey by Norman D. Price and George Rigby, Cadastral Engineers, under Group #282, Surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11383-84)

-----  
 (After a careful investigation, it is developed that Gesner's recorded retracement of this line is entirely fictitious, that it is a deliberate fabrication on his part for the purpose of justifying his own work and creating a limiting boundary for T21S R9W., and is therefore rejected as a suitable basis for restoration of lost corners referring to T21S R8W.) (Vol. 27 Pg. 11379)

The closing cor. of secs. 13 & 24, the locus of which is determined by reference to the record distance from the old SE. bearing tree, record bearing from the old SW. bearing tree, and record bearing and distance from the old NW. bearing tree.

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

	T 21 S	T 21 S
	S 13	R 8 W
C C	S 24	S 19
	R 9 W	
	1945	

from which

A dead Hemlock 42" dia., bears S.24°E., 21 lks. dist. with blaze healed. (Old BT)

A dead Hemlock 18" dia., bears S.36°W., 52 lks. dist. with partial scribe marks visible on partially healed old blaze. (Old BT)

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION C C for Secs. 13 & 24 only, T21-9

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

A dead Hemlock 12" dia., bears N.47°E., 33 lks. dist. with partial scribe marks remaining on charred face of old blaze. (Old BT)  
No other accessories available.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #'s 350 & 511, surveyed Apr. 1966/May 1967 (DCSO records Vol. 34 Page(s) 14208)

-----  
The closing cor., monumented with an iron post 2" dia., extending 8" above ground, firmly set, with brass cap mkd. in 1945,  
from which the original bearing trees:  
A decayed Hemlock stump, size indeterminate, bears S.35°E., 21 lks. dist., with no marks remaining. (1945 rec. S.24°E.)  
A decayed Hemlock stump 20" dia., bears S.36°W., 52 lks. dist., with old axe marks visible on decayed blaze.  
A decayed Hemlock stump 30" dia., bears N.47°W., 33 lks. dist. with no marks remaining.  
and new bearing trees:  
A Fir 6" dia., bears S.82°W., 33 lks. dist. mkd. T21S R9W S24 CC BT.  
A Fir 6" dia., bears N.17°W., 68 lks. dist. mkd. T21S R9W S13 CC BT.

Clyde Mulkins, L.S. #2006 - For: IP Timber Lands Operating Co. LTD - Oct. 1995 - M 123-22

-----  
Cor. for Secs. 13 & 24, T21-9 only (amended)  
Set 3/4"x36" alum. rod with a 3/4" I.P.T.O. alum. cap with magnetic insert.  
15" D.Fir, bears N.44°E., 13.9', scribed "AM CC X BT".  
From which the 1945 brass cap set by G.L.O. bears: S.89°53'E., 2.71, and at the corner was found:  
1945 GLO brass cap.  
15" D.Fir, bears N.15°W., 45.4', w/healed face. (Orig. Unknown)  
New BTs -  
13" D.Fir, bears N.38°W., 13.8', scribed "T21S R9W S13 CC BT".  
16" D.Fir, bears S.42°W., 9.4', scribed "T21S R9W S24 CC BT".  
15" D.Fir, bears S.11°W., 16.8', scribed "T21S R9W S24 CC BT".