

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 12 only, T21-9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #'s 350 & 511, surveyed Apr. 1966/May 1967 (DCSO records Vol. 34 Page(s) 14211)

Point for the ¼ sec. cor. of sec. 12 only, T21S R9W, established at midpoint latitudinally on the E. bdy. of sec. 12.

Set an iron post 28" long, 2½" dia., 24" in the ground with brass cap marked:

¼
T 21 S |
S 12 |
R 9 W |
1967

from which

A Fir 4" dia., bears N.13°W., 118 lks. dist. mkd. ¼ S12 BT.

A Fir 5" dia., bears S.3°W., 110 lks. dist. mkd. ¼ S12 BT.

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - April 16, 1987 - C.S. File 62/40-14

Found - 1967 BLM 3½" brass cap on a 2½" I.P., protruding 2" above ground, properly marked.

4" now 10" dia. D.Fir with a fully healed double blaze, bears N.12°W., 76.0 ft. (agrees with L. Roberts condition report, C.S. 63/18) (1967 resurvey, N.13°W., 77.9 ft.)

5" now 18" dia. D.Fir with a fully healed double blaze, bears S.3°W., 72.6 ft. (agrees with 1967 BLM resurvey)

1945 GLO brass cap/I.P. bears North 79.7 ft. (agrees with L. Roberts 1985 condition report.) (1967 resurvey shows a distance of 80.52 ft. W. 1/4 S7 T21S R8W)

Witness post and sign set by Roberts in 1985 bears East, 1½ ft. (C.S. 63/18 and M 99-32)

New BTs- 16" dia. D.Fir double blazed, scribed "¼ S12 CS BT", bears N.88½°W., 39.9 ft.

4" dia. Cherry tree, double blazed, scribed "X BT" bears S.3°W., 39.0 ft.

Cor. lies approx. 100 ft. South of an E-W ridge on a steep SE. slope.

continued next page

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 100539

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 12 only, T21-9

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Mark Smalley - 11/2000 - C.S. File 65/33-16

Found - 1967 BLM BC/IP

23" Fir, S.3°W., 72.4 ft., good healed face.

26" Fir, N.88½°W., 39.9 ft., good healed face.

11" Fir, N.12°W., 76.0 ft., fair healed face.

New BT - 17" Fir, N.24°E., 16.3 ft., scribed "¼ S BT"

Found brass cap & 4 BTs & 1 down BT - by Gary Smither, 2/2005
- C.S. File 65/54-10