

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 7 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 2 Page(s) 890-91)

Set post 4" dia., 4 ft. long with marked stone, 12" in ground for 1/4 sec. cor., marked 1/4 S on W. face, from which
A Fir 40" dia., bears S.65°E., 17 lks. dist. mkd. 1/4 S BT.
A Fir 6" dia., bears S.55°W., 10 lks. dist. mkd. 1/4 S BT.

GLO Resurvey by Norman D. Price and George Rigby, Cadastral Engineers, under Group #282, Surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11386)

Proportional measurement.
Set an iron post, 3 ft. long, 1" dia., 28" in the ground for 1/4 sec. cor. of sec. 7 only, with brass cap mkd: | 1/4 S 7
1945
from which
A Fir 24" dia., bears N.64 1/4°E., 31 lks. dist., mkd. 1/4 S 7 BT.
A Fir 37" dia., bears S.57 1/4°E., 165 lks. dist. mkd. 1/4 S 7 BT.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #'s 350 & 511, surveyed Apr. 1966/May 1967 (DCSO records Vol. 34 Page(s) 14211-12)

The 1/4 sec. cor., monumented with an iron post 1" dia., extending 12" above ground, firmly set, with brass cap marked in 1945,
from which bearing trees mkd. in 1945:
A sawed Fir stump 25" dia., bears N.67 1/4°E., 31 lks. dist. with healed blaze.
A sawed Fir stump 46" dia., bears S.57 1/4°E., 165 lks. dist. with no marks remaining.
and new bearing trees:
A Fir 5" dia., bears N.56 1/2°E., 92 lks. dist. mkd. 1/4 S 7 BT.
A Maple 6" dia., bears S.83°E., 50 lks. dist. mkd. 1/4 S 7 BT

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - April 16, 1987 - C.S. File 62/40-13

Found - 1945 GLO 2 1/2" brass cap on a 1" I.P., loosely set and leaning 4" North, protruding 12" above ground, properly marked. Cap is facing South, which makes sec. 7 appear West of corner.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

(All distances and bearings to plumb position of brass cap/iron pipe)

Found - 24" now 25" dia. 2 ft. high burned and rotted D.Fir stump with a partial blaze visible, bears N.64 $\frac{1}{4}$ °E., 20.5 ft. (agrees well with 1945 resurvey record) (N.67 $\frac{1}{4}$ °E., 20.5 ft. per 1967 resurvey)

37" now 46" dia. 4 ft. high burned and rotted D.Fir stump, no marks or blazes found, bears S.57 $\frac{1}{4}$ °E., 108.9 ft. (agrees well with record) 1945 BT

5" now 15" dia. D.Fir with a fully healed single blaze, bears N.56 $\frac{1}{2}$ °E., 61.5 ft. (Rec. N.56 $\frac{1}{2}$ °E., 60.7 ft. dist. is a face measurement) 1967 BT.

6" Maple, burned and gone, small Maples growing from roots near bearing and distance per 1967 resurvey

Witness post and sign bears East, 1 $\frac{1}{2}$ ft. Set by L. Roberts in 1985 condition report. C.S. 63/18

East $\frac{1}{4}$ sec. cor. for 12 only, T21-9, 1967 BLM BC/IP, bears South 79.7 ft. (agrees well with Roberts 1985 report) (1967 resurvey shows a dist. between BC/IP as 80.52 ft.)

1945 GLO cap and pipe are returned to plumb position and is surrounded by a 2 ft. dia. 1 ft. high mound of sandstone. Brass cap faces South.

(A search was made for original evidence but none was found.)

New BTs- 14" D.Fir with a double blaze, scribed " $\frac{1}{4}$ S7 CS BT", bears N.1 $\frac{1}{4}$ °E., 23.8 ft.

13" dia. D.Fir with a double blaze, scribed " $\frac{1}{4}$ S7 CS BT", bears N.82°E., 21.1 ft.

Brass cap/IP is approx. 30 ft. South of an E-W ridge on a steep SE. slope.