

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608 -dated April 17, 1893 - (DCSO records Vol. 3 Page(s) 926)

I set Fir post 4½ ft. long, 4" sq., 24" in the ground on steep hill side sloping East at the point of intersection for closing cor. to secs. 1 and 12, marked CC T21S on the W.; R9W S12 on the S.; and S1 on the N. sides, with 5 grooves on the S. and 1 groove on the N. sides, from which

- A Fir 20" dia., bears N.76°E., 12 lks. dist. mkd. CC T21S R9W S1 and 12 BT.
- A Fir 12" dia., bears S.66°W., 42 lks. dist. mkd. T21S R9W S12 BT.
- A Fir 10" dia., bears N.73°W., 29 lks. dist. mkd. T21S R9W S1 BT.

GLO Resurvey by Norman D. Price and George Rigby, Cadastral Engineers, under Group #282, Surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11386-87)

(After a careful investigation, it is developed that Gesner's recorded retracement of this line is entirely fictitious, that it is a deliberate fabrication on his part for the purpose of justifying his own work and creating a limiting boundary for T21S R9W., and is therefore rejected as a suitable basis for restoration of lost corners referring to T21S R8W.) (Vol. 27 Pg. 11379)

The closing cor. of secs. 1 and 12, the badly decayed remains of a wooden post, on which only traces of axe marks and scribe marks were found.

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

	T 21 S	T 21 S
	S 1	R 8 W
CC	S 12	S 7
	R 9 W	

1945

from which

- A Fir 24" dia., bears N.76°E., 12 lks. dist., an old bearing tree on which I uncover and obliterate the scribe marks CC T21S R9W S1 & S12 BT.
- A Fir 15" dia., bears S.64½°W., 37 lks. dist., an old bearing tree with the scribe marks BT uncovered.
- A Fir stub 9" dia., bears N.62°45'W., 27 lks. dist., mkd. T21S R9W S1 BT. (Old BT)
- A Fir 34" dia., bears N.39°45'W., 67 lks. dist. mkd. T21S R9W S1 CC BT. (New BT) (Cont. Next Page)

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 100579

PRIMARY CORNER DESCRIPTION C C for Secs. 1 & 12 only, T21-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 24" dia., bears S.70¼°W., 46 lks. dist. mkd. T21S
R9W S12 CC BT. (New BT)

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under
Group #'s 350 & 511, surveyed Apr. 1966/May 1967 (DCSO
records Vol. 34 Page(s) 14212)

The closing cor., monumented with an iron post 2" dia.,
extending 14" above ground, firmly set, with brass cap mkd.
in 1945,

from which the remaining original bearing trees:

A Fir 42" dia., bears N.76°E., 12 lks. dist., with healed
blaze.

A sawed Fir stump 18" dia., bears S.64½°W., 37 lks. dist.,
with healed blaze.

and bearing trees marked in 1945:

A burned Fir stump 30" dia., bears S.70¼°W., 46 lks.
dist., with no marks remaining.

A sawed Fir stump 30" dia., bears N.39 3/4°W., 67 lks.
dist., with healed blaze.

Raise a mound of stone, 4 ft. base, 2 ft. high, West of
corner.