

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7 only (West)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 2 Page(s) 891)

Set post 6" dia., 4 ft. long, with marked stone 12" in ground for cor. to sec. 1, 12, 6 and 7, marked T21S S6 on NE.; R8W S7 on SE.; R9W S12 on SW.; S1 on NW. faces, with 1 notch in N. and 5 in S. edges, from which
A Fir 12" dia., bears N.34°E., 8 lks. dist., mkd. T21S R8W S6 BT.
A Fir 10" dia., bears S.66°W., 6 lks. dist. mkd. T21S R9W S12 BT.
A Fir 10" dia., bears N.56°W., 31 lks. dist. mkd. T21S R9W S1 BT.
A Fir 10" dia., bears S.85°E., 26 lks. dist. mkd. T21S R8W S7 BT.

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608 -dated April 17, 1893 - (DCSO records Vol. 3 Page(s) 925-26)

Cor. to secs. 6 & 7, T21S R8W. Post had been destroyed. I re-establish as follows. Set Fir post 4½ ft. long, 5" sq., 24" in the ground on stee hill side sloping E. marked T21S S6 on the NE.; and R8W S7 on the SE. faces with 5 notches on the S. and 1 notch on the N. edges, from which
A Fir 12" dia., bears N.34°E., 8 lks. dist. mkd. T21S R8W S6 BT.
A Fir 12" dia., bears S.85°E., 26 lks. dist. mkd. T21S R8W S7 BT.
A Fir 10" dia., bears N.62°W., 31 lks. dist. mkd. T21S R9W S12 BT.
The other bearing tree had been destroyed. The description of this cor. practically agrees with notes furnished me.

GLO Resurvey by Norman D. Price and George Rigby, Cadastral Engineers, under Group #282, Surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11387)

(After a careful investigation, it is developed that Gesner's recorded retracement of this line is entirely fictitious, that it is a deliberate fabrication on his part for the purpose of justifying his own work and creating a limiting boundary for T21S R9W., and is therefore rejected as a suitable basis for restoration of lost corners referring to T21S R8W.) (Vol. 27 Pg. 11379)

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7 only (West)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

The cor. of secs. 6 & 7, the decayed and partially burned remains of a wooden stake on which axe marks and partial scribe marks were found.

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T 21 S T 21 S
R 9 W S 6
S 1 S 7
R 8 W
1945

from which

I find the old NE., SE., and NW. bearing trees uprooted and practically destroyed by fire.

A Fir 26" dia., bears N.42½°E., 36 lks. dist. mkd. T21S R8W S6 BT. (New BT)

A Fir 18" dia., bears S.4½°E., 51 lks. dist. mkd. T21S R8W S7 BT. (New BT)

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #'s 350 & 511, surveyed Apr. 1966/May 1967 (DCSO records Vol. 34 Page(s) 14212-13)

The cor. of secs. 6 & 7 only, determined at record bearing and distance from a bearing tree mkd. in 1945:

A Fir 25" dia., bears S.4½°E., 51 lks. dist. with fragmentary scribe marks visible on partly healed blaze.

and a bearing tree of which I have no record:

A Fir 37" dia., bears N.77°E., 36 lks. dist. with scribe marks T21S R8W S6 visible on open and burned blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 20" in the ground, with brass cap mkd:

T 21 S T 21 S
R 9 W S 6
S 1 S 7
R 8 W
1966

Survey by Donald Bentz, LS #839 - For: International Paper Co. - Oct. 1989 - M 101-62

Found - Brass cap, 1966 USGLO.

New BTs- 10" Alder bears N.67°W., 19.4 ft., scribed.

12" Alder bears N.66°E., 48.2 ft., scribed.

10" Alder bears S.62°E., 33.2 ft., scribed.

continued next page

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7 only (West)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Gary Smither - Dec. 2000 - C.S. File 65/33-21

Found - 1966 brass cap on iron pipe firmly set with an alum. post with an International Paper sign driven alongside the brass cap.

37" Fir, now 46" in dia., N.77°E., 36 lks., with opened & burned face & tag, found in 1966.

18" Fir, S.4½°E., 51 lks., taken in 1945 & recovered in 1966 is **gone.**

10" Alder, N.67°W., 19.4 ft. with visible scribed on open face, with tag, taken in 1989.

12" Alder, now 13" in dia., N.66°E., 48.2 ft., with visible scribes on open face, w/tag taken in 1989

10" Alder, taken in 1989, S.62°E., 33.2 ft, is **gone.**

New BT - 12" Alder, N.33°W., 19.0 ft. to spike driven in side center, marked "X" at breast height & bark scribed "BT" at base with BT tag.