

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 6 only

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 2 Page(s) 891)

Set post 4" dia., 4 ft. long, with marked stone 12" in ground for ¼ sec. cor. marked ¼ S on W. face, from which
A Fir 20" dia., bears S.70°W., 54 lks. dist. mkd. ¼ S BT.
A Cedar 18" dia., bears S.65°E., 12 lks. dist. mkd. ¼ S BT.

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608 -dated April 17, 1893 - (DCSO records Vol. 2 Page(s) 893)

The ¼ sec. cor. which is a post, 3" sq., 30" above ground marked ¼ S on the W. face, from which
A Fir 20" dia., bears S.70°W., 54 lks. dist. mkd. ¼ S BT
A Fir 18" dia., bears S.65°E., 13 lks. dist. mkd. ¼ S BT

GLO Resurvey by Norman D. Price and George Rigby, Cadastral Engineers, under Group #282, Surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11388)

(After a careful investigation, it is developed that Gesner's recorded retracement of this line is entirely fictitious, that it is a deliberate fabrication on his part for the purpose of justifying his own work and creating a limiting boundary for T21S R9W., and is therefore rejected as a suitable basis for restoration of lost corners referring to T21S R8W.) (Vol. 27 Pg. 11379)

Proportional measurement.
Set an iron post 3 ft. long, 1" dia., 28" in the ground for ¼ sec. cor. of sec. 6 only, with brass cap mkd. ¼ S 6
1945

from which
A Cedar 30" dia., bears N.88°E., 146 lks. dist. mkd. ¼ S6 BT.
A Fir 28" dia., bears S.35½°E., 122 lks. dist. mkd. ¼ S6 BT.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #'s 350 & 511, surveyed Apr. 1966/May 1967 (DCSO records Vol. 34 Page(s) 14213)

The ¼ sec. cor., monumented with an iron post 1" dia., extending 8" above ground, firmly set, with brass cap mkd. in 1945,
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 6 only

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

from which a bearing tree marked in 1945:
A Fir snag 26" dia., bears S.35½°E., 122 lks. dist. with no marks visible on opened and burned blaze.
a bearing tree of which I have no record:
An Alder 8" dia., bears S.85°E., 87 lks. dist. with scribe marks ¼ S6 BT visible in the bark.
and a new bearing tree:
A Fir 5" dia., bears N.85°E., 45 lks. dist. mkd. ¼ S6 BT.

Gary Smither - Dec. 2000 - C.S. File 65/33-22

Found - 1945 brass cap on iron pipe firmly set with red steel fence post driven alongside the brass cap.
1966 5" Fir, now 15" dia., N.85°E., 45 lks., with BLM tag & healed face, we place new tag.
8" Alder fd. in 1966, now 16" dia. S.85°E., 87 lks., with BLM tag & old bark scribe visible at base of tree. We place new bark scribe "¼ S6 BT" above old scribe with a new BT tag.
The 28" Fir taken in 1945 at S.35½°E., 122 lks. is still standing but has broken off & is badly decayed.
New BT - 12" Fir, S.84°E., 18.9 ft. to spike driven in side center, mkd: "¼ S6 BT; with BT tag.
18" Fir, N.55°E., 10.6 ft. to spike driven in side center, mkd: "¼ S6 BT" with BT tag.