

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 122100

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. Section 6 only, T22-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by W. H. Byars, under Contract #202, dated March 11, 1874 (DCSO records Vol. 2 Page(s) 835 and Vol. 4, Page 1589)

Marked a Fir tree, 14" dia., for the ¼ sec. cor.

GLO survey by Norman D. Price, Cadastral Engineer and Geo Rigby, Assoc Cadastral Engineer, under Group #282, surveyed May/Aug. 1945 (DCSO records Vol. 27 Page(s) 11374)

(39.79 CHS.)

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for witness cor. to the ¼ sec. cor. of sec. 6 only, with brass cap marked:

WC ¼ S 6
1945

from which

A Fir 32" dia., bears S.36½°E., 27 lks. dist., mkd. W C ¼ S 6 BT.

A Fir 28" dia., bears S.68°W., 94 lks. dist., mkd. W C ¼ S 6 BT.

(39.89 CHS.) (N.87°53'E)

The ¼ sec. cor. of sec. 6 only, a W. Fir 20" dia., mkd. on bark ¼ S on S. side. I re-blaze and re-mark ¼ S 6 on S. side.

(No accessories)

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone & Wm. Stoffel, crew - Sept. 1963 - C.S. File 52/14-25

Found - Brass cap set in 1945. (W.C.)
Both BTs mkd. in 1945, uprooted stump only. Both show good scars.

¼ Corner, W. Fir tree, uprooted and down.

New BTs -9" W.Fir S.25½°W., 36.0 ft. mkd. W C ¼ S 6 CS BT.

7" W.Fir S.18°W., 43.2 ft. mkd. W C ¼ S 6 CS BT.