

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 30 & 31

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 874)

Set post 4" dia., 4 ft. long with marked stone 12" in ground for 1/4 sec. cor. marked 1/4 S on N face from which:

- Fir, 10" dia., bears S.40°E., 10 lks., mkd: 1/4 S BT.
- Fir, 10" dia., bears N.38°W., 19 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Norman D. Price, Cadastral Eng. & Geo. F. Rigby, Assoc. Cadastral Eng., under group #282, surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11416)

Proportional measurement

Set an iron post, 3' long, 1" dia., 28" in the ground, for 1/4 sec. cor., with brass cap marked:

1/4 $\frac{S \ 30}{S \ 31}$
1945

from which

- A dead Fir, 60" dia., bears N.81°E., 81 lks., mkd: 1/4 S30 BT.
- A dead Fir, 34" dia., bears S.48 1/2°W., 50 lks., mkd: 1/4 S31 BT.