TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 876-5)

Set post 4" dia., 4 ft. long with marked stone 12" in ground for ¼ sec. cor. marked ¼ S on N face from which:
Fir, 30" dia., bears S.45°E., 16 lks., mkd: ¼ S BT.
Fir, 40" dia., bears N.85°W., 65 lks., mkd: ¼ S BT.

BLM dependent resurvey by Norman D. Price, Cadastral Eng. & Geo. F. Rigby, Assoc. Cadastral Eng., under group #282, surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11419)

Proportional measurement
Set an iron post, 3' long, 1" dia., 28" in the ground, for ¼ sec. cor., with brass cap marked:

¼ S 19 / S 30 / 1945

from which
A Fir, 32" dia., bears N.40°E., 49 lks., mkd: ¼ S19 BT.
A Fir, 36" dia., bears S.78°E., 73 lks., mkd: ¼ S30 BT.

Ron Rice, Ward NW - Ben Pastor - 2/19/2003 - CS File 65/45-6

Found - 1945 BC
BTs established by BLM in April 2000
14" D.Fir bears N.9°E., 16.2 ft. scribing visible.
8" D.Fir bears S.53°E., 14.3 ft. scribing visible.
New BTs- 11" D.Fir bears N.77°E., 16.5 ft. scribed "¼ S19 BT"
8" D.Fir bears S.47°W., 3.1 ft. scribed "¼ S30 BT"
All BTs painted & tagged.
Post set near corner.

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #1000, surveyed May 1999/April 2000 - (DCSO rec. Vol. 54 Page(s) 20747)

The ¼ sec. cor. of secs. 19 and 30, monumented with an iron post, 1" dia., firmly set, projecting 12" above the ground, with brass cap mkd.
from which the remains of a BT mkd. by Price and Rigby
A root hole, 35" dia., bears N.40°E., 32.3 ft., with fir log alongside with a healed blaze.
and new bearing trees
A fir, 13" dia., bears N.9°E., 16.2 ft., mkd. ¼ S19 BT.
A fir, 7" dia., bears S.63°E., 14.3 ft., mkd. ¼ S30 BT.