

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1590)

-----  
Set a Yew post 60" long, 6" dia., 24" in ground for cor. to secs. 5, 6, 31 and 32, from which  
A Fir 48" dia., bears N.50°E., 32 lks. dist.  
A Hemlock 14" dia., bears S.75°E., 30 lks. dist.  
A Hemlock 8" dia., bears S.15°W., 38 lks. dist.  
An Alder 12" dia., bears N.64°W., 48 lks. dist.

GLO resurvey by Norman D. Price, Cadastral Engineer and Geo. Rigby, Assoc. Cadastral Engineer, under Group #282, surveyed May/Aug. 1945 (DCSO records Vol. 27 Page(s) 11375)

-----  
The corner of secs. 5 & 6, the locus of which is determined at the record bearing from the old NE. BT and the record measurements from the old SE. and SW. BTs.

At point for corner  
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 5 and 6, with brass cap mkd: T 21 S R 8 W  
S 31  
S 6 S 5  
T 22 S R 8 W  
1945

from which  
A badly burned dead Fir 54" dia., bears N.50°E., 41 lks. dist. on which no marks remain. (Old BT.)  
A dead Hemlock 24" dia., bears S.69°E., 30 lks. dist. on which I uncover the scribe marks S R 8 W. (Old BT)  
A dead Hemlock 18" dia., bears S.8°W., 38 lks. dist. on which I uncover the scribe marks BT. (Old BT)  
A Fir 60" dia., bears S.7½°E., 487 lks. dist. mkd. T22S R8W S5 BT. (New BT)  
A Fir 40" dia., bears S.56°45'W., 220 lks. dist. mkd. T22S R8W S6 BT. (New BT)

BLM resurvey by Floyd A. Brooks and James E. Jelley, Cadastral Surveyors, under Group #'s 514 and 350, surveyed June 1963/March 1965 (DCSO records Vol. 33 Page(s) 13679-80)

-----  
The cor. of secs. 5 and 6, monumented with an iron post, 2" dia., 8" above ground, firmly set, with 1945 brass cap. from which the remaining original bearing tree,  
A sawed Fir stump 60" dia., bears N.50°E., 41 lks. dist. with no marks remaining.  
bearing trees mkd. by Price,  
(Cont. Next Page)

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 162100

PRIMARY CORNER DESCRIPTION C C for Secs. 5 and 6 only, T22-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A sawed Fir stump 65" dia., bears S.7½°E., 487 lks. dist. with fragmentary scribe marks visible on burned face of blaze.

A sawed Fir stump 45" dia., bears S.56 3/4°W., 220 lks. dist. with scribe marks R8W S visible on burned face of blaze.

and a new bearing tree,

A sawed Fir stump 35" dia., bears S.44½°W., 91 lks. dist. mkd. T22S R8W S6 BT.

Set a 7 ft. steel fence post, 2 ft. in the ground, alongside the iron post.