TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 31 & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 872)

Set post 4" dia., 4 ft. long with marked stone 12" in ground for ¼ sec. cor. marked ¼ S on W face from which:
Fir, 6" dia., bears S.57°E., 26 lks., mkd: ¼ S BT.
Fir, 30" dia., bears S.60°W., 5 lks., mkd: ¼ S BT.

BLM dependent resurvey by Norman D. Price, Cadastral Eng. & Geo. F. Rigby, Assoc. Cadastral Eng., under group #282, surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11414)

Proportional measurement
Set an iron post, 3' long, 1" dia., 28" in the ground, for ¼ sec. cor., with brass cap marked: ¼
S 31|S 32
1945 from which
A Fir, 30" dia., bears N.65¼°E., 312 lks., mkd: ¼ S32 BT.
A Fir, 30" dia., bears S.35¼°W., 85 lks., mkd: ¼ S31 BT.