TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 877)

Set post 4" dia., 4 ft. long with marked stone 12" in ground for ¼ sec. cor. marked ¼ S on W face raised mound of stone alongside.

No witness trees.

BLM dependent resurvey by Norman D. Price, Cadastral Eng. & Geo. F. Rigby, Assoc. Cadastral Eng., under group #282, surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11420)

Proportional measurement

Set an iron post, 3' long, 1" dia., 28" in the ground, for ¼ sec. cor., with brass cap marked:

¼
S 19|S 20
1945

from which

A dead fir, 70" dia. bears N.18½°E., 57 lks. mkd: ¼ S20 BT

A dead fir, 60" dia., bears N.42°W., 76 lks. mkd: ¼ S19 BT

Ron Rice - 3/27/2006 - C.S. File 65/58-14

Found - 1945 2½" GLO brass cap (properly mkd) with the following accessories:
70" rotted D.Fir stump bears N.18½°E., 37.6 ft. (rotted face)
60" rotted D.Fir stump bears N.42°W., 50.2 ft. (rotted face)

New - 23" D.Fir bears N.7½°E. 32.98 ft. scribed "¼ S20 BT"
18" D.Fir bears N.70¼°E. 23.26 ft scribed "¼ S20 BT"
17" D.Fir bears N.76°W., 11.99 ft scribed "¼ S19 BT"
23" D.Fir bears N.47¼°W. 43.36 ft scribed "¼ S19 BT"
5½" galvanized steel post is set adjacent to corner.
All BTs have red painted bands & yellow BT tags.