

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Cor. Secs. 17, 18, 19, & 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 877)

Set post 6" dia., 4 ft. long on mound of stone 18" high, 5 ft. sq. at base for corner to secs. 17, 18, 19 & 20, marked T21S, S 17 on NE, R8W, S 20 on SE, S 19 on SW, S 18 on NW face with 5 notches on E & 3 on S edge.

BLM dependent resurvey by Norman D. Price, Cadastral Eng. & Geo. F. Rigby, Assoc. Cadastral Eng., under group #282, surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11420)

Proportional measurement
Set an iron post, 3' long, 1" dia., 28" in the ground, for cor. of secs. 17, 18, 19, & 20, with brass cap marked:
T21S R8W
S 18|S 17
S 19|S 20
1945

- from which
- A hemlock, 10" dia., bears N.50°E., 147 lks., mkd: T21S R8W S17 BT.
 - A fir, 62" dia., bears S.36°E., 168 lks., mkd: T21S R8W S20 BT.
 - A fir, 48" dia., bears S.38°W., 203 lks., mkd: T21S R8W S19 BT.
 - A fir, 25" dia., bears N.45°W., 174 lks., mkd: T21S R8W S18 BT.

BLM remonumentation of certain orig. cor. pts by Wm.. Glenn & James Jelley, Cadastral Surveyors, under group #s 350 & 635, surveyed April/May 1967-(DCSO records C.S. File 65/27-1)

The cor. of secs. 17, 18, 19, & 20, monumented with an iron post, 2" dia., firmly set, projecting 8" above ground, with brass cap properly marked,
from which

- A burned fir, 62" dia., bears S.36°E., 168 lks., with healed blaze.
 - A fir, 30" dia., bears N.45°W., 174 lks., with fragmentary scribe marks visible on partially healed blaze.
- and new bearing trees
- A fir, 17" dia. bears N.83°E. 83 lks. mkd: T21S R8W S17 BT
 - A maple, 20" dia., bears S.12°E., 23 lks., mkd: T21S R8W S20 BT.
 - A cedar, 15" dia., bears S.67°W., 85 lks., mkd: T21S R8W S19 BT.

Set a 6' steel fence post alongside the iron post.

