

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 18

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 880)

Set post 4" dia., 4 ft. long with marked stone 12" in ground for 1/4 sec. cor. marked 1/4 S on W face from which:

Fir, 4" dia., bears N.27°E., 42 lks., mkd: 1/4 S BT.

Fir, 7" dia., bears N.16°W., 91 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Norman D. Price, Cadastral Eng. & Geo. F. Rigby, Assoc. Cadastral Eng., under group #282, surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11423)

Proportional measurement

Set an iron post, 3' long, 1" dia., 28" in the ground, for 1/4 sec. cor., with brass cap marked:

1/4
S 18|S 17
1945

from which

A dead fir, 60" dia. bears N.4°E., 58 lks., mkd: 1/4 S17 BT.

A dead fir, 52" dia. bears S.42 1/2°W., 76 lks. mkd: 1/4 S18 BT

BLM remonumentation of certain orig. corner points by Wm. W. Glenn & James E. Jelley, Cadastral Surveyors, under group #s 350 & 635, surveyed April/May 1967 - (DCSO records C.S. File 65/27-1)

The 1/4 sec. cor. of secs. 17 & 18, monumented with an iron post, 1" dia., firmly set, projecting 6" above ground, with brass cap properly marked,

from which bearing trees marked in 1945

A burned fir stump, 60" dia., bears N.4°E., 58 lks., no marks remaining on burned blaze.

A burned fir stump, 52" dia., bears S.42 1/2°W., 76 lks., no marks remaining on burned blaze.

and new BTs

A fir, 5" dia., bears N.63 1/2°E., 6 lks., mkd: 1/4 S17 BT.

A fir, 5" dia., bears S.50°W., 34 lks., mkd: 1/4 S18 BT.

Set a 6' steel fence post alongside the iron post.

Rob Ward - For: Roseburg Resources Co. - April 2002 - M140-10

Found - 2 1/2" GLO brass cap dated 1945

14" D.Fir bears N.63 1/2°E. 6 lks. -healed face

17" D.Fir bears S.50°W. 34 lks. -healed face

New BTs- 12" D.Fir bears S.2°E. 12.2' blazed/scribed: 1/4 S17 BT

13" D.Fir bears N.5°W. 18.7' blazed/scribed: 1/4 S18 BT