

PRIMARY CORNER DESCRIPTION Cor. Secs. 7, 8, 17, & 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 880)

Set post 6" dia., 4 ft. long with marked stone 12" in ground for corner to secs. 7, 8, 17, & 18, marked T21S, S 8 on NE, R8W, S 17 on SE, S 18 on SW, S 7 on NW face with 5 notches on E & 4 on S edge from which:

- Fir, 10" dia. bears N.20°E., 14 lks., mkd: T21S R8W S8 BT.
- Fir, 16" dia. bears S.30°E., 14 lks., mkd: T21S R8W S17 BT
- Fir, 14" dia. bears S.25°W., 45 lks. mkd: T21S R8W S18 BT
- Fir, 5" dia., bears N.32°W., 50 lks., mkd: T21S R8W S7 BT.

BLM dependent resurvey by Norman D. Price, Cadastral Eng. & Geo. F. Rigby, Assoc. Cadastral Eng., under group #282, surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11423)

Proportional measurement

Set an iron post, 3' long, 1" dia., 28" in the ground, for cor. of secs. 7, 8, 17, & 18, with brass cap marked:

T21S R8W
S 7 | S 8
S 18 | S 17
1945

from which

- A fir, 20" dia. bears N.31°E., 35 lks. mkd: T21S R8W S8 BT
- A fir, 20" dia., bears S.54¼°E., 48 lks., mkd: T21S R8W S17 BT.
- A fir, 24" dia., bears S.57°45'W., 131 lks., mkd: T21S R8W S18 BT.
- A fir, 30" dia. bears N.17°W. 134 lks. mkd: T21S R8W S7 BT

BLM remonumentation of certain corner points by Floyd Brooks, Cadastral Surveyor, under Group No. 350, surveyed April 18, 1960 (DCSO records Vol. 30 Page(s) 12888)

The cor. of secs. 7, 8, 17, & 18, determined at record bearing & distance from each of the BTs marked in 1945:

- A sawed fir stump, 26" dia., bears N.31°E., 35 lks., with fragmentary scribe marks visible on burned blaze.
- A decayed fir stump, 28", bears S.54¼°E., 48 lks., with scribe marks T21S R8W S17 BT visible.
- A fallen & decayed fir, size indeterminate, bears S.57 3/4°W., 131 lks., with no marks remaining.
- A sawed fir stump, 43" dia., bears N.17°W., 134 lks., with no marks remaining.

At the corner point

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 7, 8, 17, & 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set an iron post, 28" long, 2½" dia., 24" in the ground, with
brass cap marked:

T21S R8W
S 7 | S 8
S 18 | S 17
1960

from which new BTs:

A fir, 15" dia. bears N.68°E. 323 lks. mkd: T21S R8W S8 BT

A fir, 40" dia., bears S.54½°E., 229 lks., mkd: T21S R8W
S17 BT.

A fir, 28" dia., bears S.81½°W., 130 lks., mkd: T21S R8W
S18 BT.

A fir, 33" dia. bears N.49°W. 139 lks. mkd: T21S R8W S7 BT

BLM remonumentation of certain orig. corner points by Wm. W.
Glenn & James E. Jelley, Cadastral Surveyors, under group #s
350 & 635, surveyed April/May 1967 - (DCSO records C.S. File
65/27-1)

The cor. of secs. 7, 8, 17, & 18, monumented with an iron
post, 2½" dia., firmly set, projecting 4" above ground, with
brass cap properly marked,
from which

A burned & sawed fir stump, 23" dia., bears N.31°E., 35
lks., with healed blaze.

A burned & sawed fir, 24" dia., bears S.54½°E., 48 lks.,
with healed blaze.

A burned & sawed fir stump, 27" dia., bears S.57 3/4°W.,
131 lks., with healed blaze.

A burned & sawed fir stump, 35" dia., bears N.17°W., 134
lks., with healed blaze.

and a BT mkd. in 1960

A fir, 40" dia., bears S.54½°E., 229 lks., with scribe
marks T21S R8W S17 BT visible on open blaze.

Set a 6' steel fence post alongside the iron post.

Gary Smithers - Jan. 2002 - C.S. File 65/42-6

Found - 1960 brass cap on iron pipe firmly set with a steel
fence post driven alongside the brass cap.

23" D.Fir stump, N.31°E., 35 lks., with visible
scribe on burnt & rotted face.

18" D.Fir stump, S.54¼°E., 48 lks, burnt & rotted,
no markings.

27" Fir stump, S.57¾°W., 131 lks. gone.

40" D.Fir stump, S.54½°E., 229 lks., with visible
scribe on open face & tag.

35" D.Fir stump, N.17°W., 134 lks., burnt & rotted
with no markings. continued next page

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Cor. Secs. 7, 8, 17, & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

17" D.Fir, N.68°E., 323 lks. with healed face & tag.
33" D.Fir, N.49°W., 139 lks., has fallen over.
28" D.Fir, S.81½°W., 130 lks., has fallen over.
New BTs- 12" D.Fir, S.62°W., 4.1 ft. to spike driven in side
center, marked "T21 R8 ¼ S18 BT", with BT tag.
11" D.Fir, N.32°W., 6.7 ft. to spike driven in side
center, marked "T21 R8 ¼ S7 BT", with BT tag.
12" D.Fir, S.43°E., 32.0 ft. to spike driven in side
center, marked "T21 R8 ¼ S17 BT", with BT tag.

Found brass cap & 8 BTs & 2 down BTs by Gary Smither, 2/2005
- C.S. File 65/54-9