

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 8

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 881)

Set post 4" dia., 4 ft. long in mound of stone 18" high, 3½ ft. sq. at base for ¼ sec. cor. marked ¼ S on N face from which:

No witness tress.

BLM dependent resurvey by Norman D. Price, Cadastral Eng. & Geo. F. Rigby, Assoc. Cadastral Eng., under group #282, surveyed May/Aug. 1945 (DCSO records Vol. 27 Page(s) 11425-6)

Proportional measurement

Set an iron post, 3' long, 1" dia., 28" in the ground, for ¼ sec. cor., with brass cap marked: ¼

S 7|S 8
1945

from which

A fir, 30" dia., bears N.85°E., 42 lks., mkd: ¼ S8 BT.

A fir, 15" dia., bears S.71½°W., 76 lks., mkd: ¼ S7 BT.

BLM remonumentation of certain orig. corner points by Wm. W. Glenn & James E. Jelley, Cadastral Surveyors, under group #s 350 & 635, surveyed April/May 1967 - (DCSO records C.S. File 65/27-1)

The ¼ sec. cor. of secs. 7 & 8, monumented with an iron post, 1" dia., firmly set, projecting 6" above ground, with brass cap properly marked,

from which bearing trees marked in 1945

A burned fir stump, 30" dia., bears N.85°E., 42 lks., with burned blaze.

A burned & sawed fir stump, 16" dia., bears S.71½°W., 76 lks., with scribe marks S7 BT visible on open burned blaze.

and new BTs

A fir, 40" dia., bears N.41½°E., 174 lks., mkd: ¼ S8 BT.

A fir, 35" dia., bears N.84°W., 208 lks., mkd: ¼ S7 BT.

Set a 6' steel fence post alongside the iron post.

Gary Smithers - Dec. 2001 - C.S. File 65/42-8

Found - 1945 brass cap on iron pipe firmly set with steel fence post driven alongside the corner.

25" burnt & rotting Fir stump, N.85°E., 42 lks.

Burnt out face w/axe marks but no visible scribe.

continued next page

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

15" Fir, S.71½°W., 76 lks., is gone. Found 24"x8" piece of wood with visible scribe.
44" Fir, N.41½°E., 174 lks., with healed face & tag.
43" Fir, N.84°W., 208 lks., with healed face & tag.
New BTs- 7" D.Fir, S.65°E., 4.3 ft. to spike side center scribed "T21 R8 ¼ S8 BT", with new BT tag.
16" D.Fir N.19°W., 17.8 ft. to spike side center scribed "T21 R8 ¼ S7 BT", with new BT tag.