

PRIMARY CORNER DESCRIPTION Cor. Secs. 5, 6, 7, & 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 881)

Set post 6" dia., 4 ft. long with marked stone 12" in ground for corner to secs. 5, 6, 7, & 8, marked T21S, S 5 on NE, R8W, S 8 on SE, S 7 on SW, S 6 on NW face with 5 notches on S & E edge from which:

- Fir, 40" dia. bears N.45°E., 10 lks., mkd: T21S R8W S5 BT.
- Fir, 40" dia., bears S.80°E., 6 lks., mkd: T21S R8W S8 BT.
- Maple, 8" dia. bears S.80°W., 48 lks. mkd: T21S R8W S7 BT
- Alder, 20" dia. bears N.13°W. 100 lks. mkd: T21S R8W S6 BT

BLM dependent resurvey by Norman D. Price, Cadastral Eng. & Geo. F. Rigby, Assoc. Cadastral Eng., under group #282, surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11426)

Proportional measurement

Set an iron post, 3' long, 1" dia., 28" in the ground, for ¼ sec. cor., with brass cap marked:

T21S R8W
S 6 | S 5
S 7 | S 8
1945

from which

- A dead fir, 70" dia., bears N.55½°E., 34 lks., mkd: T21S R8W S5 BT.
- A dead fir, 50" dia., bears S.70¼°E., 97 lks., mkd: T21S R8W S8 BT.
- A dead fir, 50" dia., bears S.16¼°W., 117 lks., mkd: T21S R8W S7 BT.
- A dead fir, 60" dia., bears N.4°45'W., 114 lks., mkd: T21S R8W S6 BT.

BLM remonumentation of certain orig. corner points by Wm. W. Glenn & James E. Jelley, Cadastral Surveyors, under group #s 350 & 635, surveyed April/May 1967 - (DCSO records C.S. File 65/27-1)

The cor. of secs. 5, 6, 7, & 8, monumented with an iron post, 2" dia., firmly set, projecting 12" above ground, with brass cap properly marked,
from which

- A fir snag, 70" dia., bears N.55½°E., 34 lks., no marks remaining on burned blaze. Rescribe T21S R8W S5 BT on new blaze.
- A burned fir stump, 50" dia., bears S.70¼°E., 97 lks., no marks remaining on burned blaze. continued next page

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor. Secs. 5, 6, 7, & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A burned fir stump, 50" dia., bears S.16¼°W., 117 lks., with scribe marks T21S R8W S7 visible on open & burned blaze.

A fir snag, 60" dia., bears N.4 3/4°W., 114 lks., no marks remaining on burned blaze.

and a new BT

A fir, 4" dia. bears N.54°W., 67 lks. mkd: T21S R8W S6 BT. Set a 6' steel fence post alongside the iron post.

Gary Smithers - Dec. 2001 - C.S. File 65/42-9

Found - 1945 brass cap on iron pipe firmly set with a steel fence post driven alongside the brass cap.

70" burnt Fir snag, N.55½°E., 34 lks., with visible scribe & tag.

50" burnt Fir stump, S.70¼°E., 97 lks., no markings.

38" burnt Fir stump, S.16¼°W., 117 lks., with faint scribe visible.

46" Fir snag, N.4¾°W., 114 lks., no markings.

21" D.Fir, N.54°W., 67 lks., with healed face & tag.

New BTs- 7" D.Fir, S.38°E., 17.7 ft. to spike side center scribed "T21 R8 ¼ S8 BT", with new BT tag.

12" Alder, S.64°W., 15.0 ft. to spike side center scribed "T21 R8 ¼ S7 BT", with new BT tag.