

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 6

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 884)

Set post 4" dia., 4 ft. long on mound of stone 18" high 3¼ ft. base for ¼ sec. cor. mkd: ¼ S on N face.

BLM dependent resurvey by Norman D. Price, Cadastral Eng. & Geo. F. Rigby, Assoc. Cadastral Eng., under group #282, surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11429)

Proportional measurement
Set an iron post, 3' long, 1" dia., 28" in the ground, for ¼ sec. cor., with brass cap marked:

¼
S 6 | S 5
1945

from which

A Fir, 36" dia., bears S.70°E., 52 lks., mkd: ¼ S5 BT.

A Fir, 40" dia., bears N.85°W., 95 lks., mkd: ¼ S6 BT.

BLM remonumentation of certain orig. corner points by Wm. W. Glenn & James E. Jelley, Cadastral Surveyors, under group #s 350 & 635, surveyed April/May 1967 - (DCSO records C.S. File 65/27-1)

The ¼ sec. cor. of secs. 5 & 6, monumented with an iron post, 1" dia., firmly set, projecting 4" above ground, with brass cap properly marked,

from which bearing trees marked in 1945

A sawed fir stump, 30" dia., bears S.70°E., 52 lks., no marks remaining on burned blaze.

and a new BT

A burned fir snag, 12" dia., bears S.89°E., 58 lks., mkd: ¼ S5 BT.

A fir, 4" dia., bears S.83½°W., 25 lks., mkd: ¼ S6 BT.

Set a 6' steel fence post alongside the iron post.

Gary Smithers - Jan. 2002 - C.S. File 65/42-4

Found - 1945 brass cap on iron pipe firmly set with steel fence post driven alongside the brass cap.

1945 36" Fir, S.70°E., 52 lks., rotting & burnt with no markings.

1945 40" Fir, N.85°W., 95 lks., rotting & burnt with no markings.

14" Fir, no rec. S.82°E., 39.0 ft., with visible scribe has fallen over. continued next page

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 200640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs- 16" D.Fir, N.48°W., 16.4 ft. to spike driven in side center, marked "T21 R8 ¼ S6 BT", with BT tag.
9" D.Fir, S.54°E., 12.2 ft. to spike driven in side center, marked "T21 R8 ¼ S5 BT", with BT tag.
9" D.Fir, N.73dE., 16.1 ft to spike driven in side center, marked "T21 R8 ¼ S5 BT", with BT tag.