

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 1 Page(s) 451)

 Set post, 6" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 31, 32, 5 & 6, marked T20S S32 on NE.; R8W S5 on SE.; T21S S6 on SW.; S31 on NW. faces, with 1 notch on W. and 5 in E. edges; from which
 Fir 8" dia., bears N.57°W., 14 lks. dist. mkd. T20S R8W S31 BT.
 Fir 6" dia., bears N.30°E., 12 lks. dist. mkd. T20S R8W S32 BT.
 Maple 10" dia., bears S.52°W., 60 lks. dist. mkd. T21S R8W S6 BT.
 Maple 9" dia., S.64°E., 10 lks. dist. mkd. T21S R8W S5 BT.

GLO Resurvey by Norman D. Price and George Rigby, Cadastral Engineers, under Group #282, Surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11390)

 The Sec. cor., which is determined at the record measurements from the old NE.; SE.; and NW. bearing trees:

At the corner point
 Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T 20	S R 8 W
S 31	S 32
S 6	S 5
T 21	S
1945	

from which
 A charred Hemlock stub, 10" dia., bears N.27½°E., 12 lks. dist., with only axe marks remaining on this old bearing tree.
 A charred Maple stump, 16" dia., bears S.62°E., 10 lks. with only axe marks remaining on this old bearing tree.
 A charred Fir stub, 11" dia., bears N.53°W., 14 lks. dist., with only axe marks remaining on this old bearing tree.
 A dead Fir 28" dia., bears N.67°E., 21 lks. dist., mkd. T20S R8W S32 BT. (New BT)
 A Fir 14" dia., bears S.36½°E., 128 lks. dist. mkd. T21S R8W S5 BT. (New BT)
 A Fir 30" dia., bears S.10°W., 176 lks. dist. mkd. T21S R8W S6 BT. (New BT)
 A Maple 14" dia., bears N.83°W., 55 lks. dist. mkd. T20S R8W S31 BT. (New BT)

(Cont. Next Page)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

BLM Remonumentation by Wm. Glenn; C. Albert White & James E. Jelley, Cadastral Surveyors, under Group #'s 350 & 635, surveyed April/May 1967 - (DCSO rec. Vol. 43 Page(s) 16708)

The Sec. cor., monumented with an iron post, 2" dia., firmly set, projecting 5" above ground, with brass cap mkd. in 1945, from which the remains of the bearing trees mkd. in 1945:

A burned Fir snag 25" dia., bears N.68½°E., 23½ lks., with no marks remaining on burned blaze. (Rec. N.67°E., 21 lks.) Rescribed "T20S R8W S32 BT" on new blaze.

A burned Fir snag 12" dia., bears S.36½°E., 128 lks., no marks remaining on burned blaze.

A burned Fir snag 27" dia., bears S.10°W., 176 lks., no marks remaining on burned blaze.

and new bearing trees:

A Fir stump 22" dia., bears S.11½°E., 67 lks., mkd. T21S R8W S5 BT.

A burned Fir snag, 25" dia., bears S.22°W., 116 lks. mkd. T21S R8W S6 BT.

A burned Fir snag 17" dia., bears N.17½°W., 55 lks. mkd. T20S R8W S31 BT.

Set a 5 ft. steel fence post alongside the iron post.

Gary Smithers - Jan. 2002 - C.S. File 65/42-10

Found - 1945 brass cap on iron pipe firmly set with steel fence post driven alongside the brass cap.

25" burnt & rotting Fir stump, N.68½°E., 23½ lks., with old tag & visible scribes.

15" burnt & rotting Fir stump, S.36½°E., 128 lks., with visible scribes.

30" burnt & rotting Fir stump, S.10°W., 176 lks., with visible scribes.

22" burnt & rotting Fir stump, S.11½°E., 67 lks., with visible scribes & old tag.

25" burnt & rotting Fir snag, S.22°W., 116 lks., with visible scribes.

17" burnt & rotting Fir snag, N.17½°W., 55 lks., with visible scribes & old tag.

New BTs- 9" D.Fir N.11°W., 2.9 ft. to spike driven in side center, mkd: "T20 R8 S31 BT" with BT tag.

9" D.Fir N.19°E., 13.5 ft. to spike driven in side center, mkd: "T20 R8 S32 BT" with BT tag.

15" D.Fir S.79°E., 18.1 ft. to spike driven in side center, mkd: "T21 R8 S5 BT" with BT tag.

9" D.Fir S.2°W., 15.8 ft. to spike driven in side center, mkd: "T21 R8 S5 BT" with BT tag.

cont.

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5 & 6; 31 & 32 T20-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Fd. BC & BTs; & steel post adjacent to corner by R. Rice
2/2014 - M167-42

Fd ok 10/2019 - R. Quimby - C.S. File 65/104-22