

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 224100

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. Section 5 only, T22-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by Floyd A. Brooks and James E. Jelley, Cadastral Surveyors, under Group #'s 514 and 350, surveyed June 1963/March 1965 (DCSO records Vol. 33 Page(s) 13678-79)

Point for the ¼ sec. cor. of sec. 5, T22S R8W at midpoint in departure on the N. bdy. of sec. 5.
Set an iron post 28" long, 2½" dia., 24" in the ground with brass cap marked:

¼ S5
T22S R8W
1963

from which

- A Fir 45" dia., bears S.31¼°E., 556 lks. dist. mkd. ¼ S5 BT.
- A Fir 44" dia., bears S.45°W., 340 lks. dist. mkd. ¼ S5 BT.

BLM remonumentation by Aaron M Graham, Cadastral Surveyor and Michael Jones Surveying Technician under Group #2199 surveyed April 2008/April 2009 - (DCSO rec Vol 56 Pgs 21933-4)

The ¼ sec. cor. of sec. 5 only, established by Brooks and Jelley in 1963-65; monumented with an iron post, 2½" dia., firmly set, projecting 3" above ground, with a brass cap (properly) mkd.

from which the remains of bearing trees mkd. by Brooks and Jelley in 1963-65

- A fir, 46" dia. bears S.31¾°E., 367.0 ft. no marks visible
- A fir stump, 50" dia., bears S.45°W., 224.4 ft. no marks visible.

and new bearing trees

- A fir, 18" dia., bears S.52°E., 10.4 ft., mkd. X BT.
- A fir, 19" dia., bears S.20°W., 7.0 ft., mkd. ¼ S5 BT.