TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 873)

Fir, 4" dia., for ¼ sec. cor. marked ¼ S on N face from which:
Fir, 36" dia., bears South 35 lks., mkd: ¼ S BT.
Fir, 50" dia., bears N.30°W., 31 lks., mkd: ¼ S BT.

BLM dependent resurvey by Norman D. Price, Cadastral Eng. & Geo. F. Rigby, Assoc. Cadastral Eng., under group #282, surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11415)

Proportional measurement
Set an iron post, 3' long, 1" dia., 28" in the ground, for ¼ sec. cor., with brass cap marked: ¼ S 29 / S 32 / 1945

from which
A Hemlock, 28" dia., bears N.43½°W., 15 lks., mkd: ¼ S29 BT.
A Hemlock, 32" dia., bears S.11½°E., 79 lks., mkd: ¼ S32 BT.

Gary Smithers - Feb. 2004 - C.S. File 65/49-20

Found - 1945 Brass Cap on Iron Pipe firmly set. We set a 6 ft. galvanized steel fence post alongside with top painted red.
Old Bearing Trees Taken in 1945 by GLO:
28" D. Fir Stump (record Hemlock), N.53°W., (record N.43½°W.), 15 links, with visible scribes and old bearing tree tag.
18" rotted D. Fir Stump (record Hemlock), S.4°E., (record S.11½°E.), 79 lks. with no visible scribe and old bearing tree tag.
New BTs- 17" D. Fir, West, 8.2 feet to spike set side center, scribed "T21R81/4S29BT"with aluminum tag
19" D.Fir, S.12°E. 20.1 ft to spike set side center, scribed "T21R81/4S32BT"with aluminum tag
15" D. Fir, N.86°E., 17.3 feet to spike set side center, scribed "T21R81/4S29BT"with aluminum tag
17" D. Fir, N.11°E., 15.5 feet to spike set side center, scribed "T21R81/4S29BT"with aluminum tag

---