

PRIMARY CORNER DESCRIPTION WC 1/4 Cor. Secs. 17 & 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 878)

Set post 4" dia., 4 ft. long on mound of stone 18" high, 3½ ft. sq. at base for ¼ sec. cor. marked ¼ S on N face.

BLM dependent resurvey by Norman D. Price, Cadastral Eng. & Geo. F. Rigby, Assoc. Cadastral Eng., under group #282, surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11421)

N.88°25'W., bet. secs. 17 & 20
39.385 chains

The proportional point for the ¼ sec. cor. falls on steep sloop with about 2" of loose soil.

43.115 chains

Set an iron post, 3' long, 1" dia., 28" in the ground, for ¼ sec. cor., with brass cap marked:

W C
¼ S 17
S 20
1945

from which

A dead fir, 70" dia., bears N.47°W., 103 lks., mkd: WC ¼ S17 BT.

A fir, 48" dia., bears S.27°E., 220 lks., mkd: WC ¼ S20 BT.

The witness corner is located on top of a sharp spur ridge which bears N. & S.

Ron Rice - 3/27/2006 - C.S. File 65/58-13

Found - 1945 2½" GLO brass cap (properly mkd) with the following accessories:

70" rotted D.Fir stump bears N.47°W., 68.0 ft. (rotted face)

50" rotted D.Fir stump bears S.27°E., 145.2 ft. (rotted face)

New - 16" D.Fir bears N.17°E., 2.65 ft.

14" D.Fir bears S.73°E., 3.8 ft.

14" D.Fir bears N.31°W., 28.25 ft.

14" D.Fir bears S.55°W., 26.0 ft.

All new BTs scribed "X" at breast height & "BT" at base.

5½" galvanized steel post is set adjacent to corner.

All BTs have red painted bands & yellow BT tags.