

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 5; & 32, T20-8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 1 Page(s) 452)

Set post 4" dia., 4 ft. long, with marked stone, 12" in ground for gr. sec. cor., marked ¼ S on N. face; from which
Fir 10" dia., bears N.28°E., 5 lks. dist. mkd. ¼ S BT.
Fir 10" dia., bears S.22°E., 20 lks. dist. mkd. ¼ S BT.

GLO Resurvey by Norman D. Price and George Rigby, Cadastral Engineers, under Group #282, Surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11391)

The ¼ sec. cor., the locus of which is determined at the record measurements from both old bearing trees.

At the corner point

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd:

¼ $\frac{S \ 32}{S \ 5}$
1945

from which

A Fir 22" dia., bears N.19¼°E., 5 lks. dist., with blaze healed. (Old BT)

A Fir 16" dia., bears S.13½°E., 20 lks. dist., with blaze healed. (Old BT)

A Fir 22" dia., bears S.76°W., 56 lks. dist., mkd. ¼ S5 BT. (New BT)

BLM Remonumentation of corner by Wm. Glenn; C. Albert White and James E. Jelley, Cadastral Surveyors, under Group #'s 350 and 635, surveyed April/May 1967 - (DCSO records Vol. 43 Page(s) 16707-08)

The ¼ sec. cor., monumented with an iron post 1" dia., firmly set, projecting 10" above ground with brass cap mkd. in 1945, from which the remains of the original bearing trees:

A burned Fir 30" dia., bears N.19¼°E., 5 lks. dist., with healed blaze.

A burned Fir snag 16" dia., bears S.13½°E., 20 lks. dist., with healed blaze.

and the remains of the bearing tree mkd. in 1945:

A burned Fir 30" dia., bears S.76°W., 56 lks. dist., no marks visible on open and burned blaze. Rescribed "¼ S5 BT" on new blaze.

Set a 5 ft. steel fence post alongside the iron post.

continued next page

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 240700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 5; & 32, T20-8

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

Found - 2½" brass cap dated 1945 with the following accessories:

25" Fir stump bears N.19¼°E., 3.3' - healed face

12" Fir snag bears S.13½°E., 13.3' - rotted face

Rotted staub bears S.76°W., 37.0' - no marks

New BTs- 11" D.Fir bears N.52°W., 5.7' - blazed, scribed ¼ S32 BT

11" D.Fir bears N.65°W., 9.8' - blazed, scribed ¼ S32 BT

16" D.Fir bears S.83°E., 15.2' - blazed, scribed ¼ S5 BT

17" D.Fir bears S.32°W., 23.4' - blazed scribed ¼ S5 BT

Steel post adjacent to corner