

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W. H. Byars under Contract #376 dated Jan. 22, 1881 (DCSO records Vol. 4 Page(s) 1604)

-----  
Intersect North bdy. of Tp. 14.20 chs. West of cor. established for secs. 32 and 33.

Marked a Fir 6" dia., for the cor. to secs. 4 and 5, from which

A Fir 36" dia., bears S.20°E., 79 lks. dist.

A Fir 12" dia., bears S.20°W., 82 lks. dist.

GLO resurvey by Norman D. Price, Cadastral Engineer and Geo. Rigby, Assoc. Cadastral Engineer, under Contract #282, surveyed May/Aug. 1945 (DCSO records Vol. 27 Page(s) 11376-77)

-----  
The closing cor. of secs. 4 & 5, T22S R8W, bears North 13 lks. dist., a D. Fir 32" dia., with surface scars on E., S., and W. sides. I re-blaze and re-mark this old tree closing corner as follows:

S 4 on E.,

C C T 22 S R 8 W on S., and

S 5 on W. side;

from which

A Fir 52" dia., bears S.16¼°E., 75 lks. dist. mkd. on bark T22S R8W S4 BT. I re-blaze and re-mark this old bearing tree "T22S R8W S4 CC BT".

The old SW BT has fallen and slidden down the mountain.

A Fir 16" dia., bears S.53½°W., 52 lks. dist. mkd. T22S R8W S5 CC BT. (New BT)

BLM resurvey by Floyd A. Brooks and James E. Jelley, Cadastral Surveyors, under Group #'s 514 and 350, surveyed June 1963/March 1965 (DCSO records Vol. 33 Page(s) 13700)

-----  
True point for the closing corner of secs. 4 and 5, on the S. bdy. of Sec. 32, T21S R8W.

Set an iron post, 28" long, 2½" dia., 24" in the ground with brass cap marked:

T 21 S R 8 W  
        S 32          
S 5 | S 4  
T 22 S R 8 W  
C C  
1963

from which

A Fir 25" dia., bears S.21 3/4°E., 173 lks. dist. mkd. T22S R8W S4 CC BT.

A Fir 8" dia., bears S.47½°W., 89 lks. dist. mkd. T22S R8W S5 CC BT. (Cont. Next Page)

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 266100

PRIMARY CORNER DESCRIPTION C C for Secs. 4 and 5 only, T22-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

From this point, the original closing corner of secs. 4 and 5, bears N.0°28'E., 0.14 chs. dist., monumented with a Fir 32" dia., with healed blazes on the S., E., and W. faces, from which the remaining original bearing tree,  
A sawed Fir stump 60" dia., bears S.18½°E., 79 lks. dist. with bottom part of healed blaze remaining. (Rec. brg. & dist. S.16¼°E., 75 lks.)  
and a bearing tree mkd. by Price in 1945  
A Fir 28" dia., bears S.50°W., 53 lks. dist., with partial scribe marks visible on opened blaze. (Rec. brg. & dist., S.53½°W., 52 lks.)

FD. OK - Les Roberts - M 124-44 & CS 65/12-5 A&B - 2-10-97

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor and Michael O. Jones Surveying Technician, under Group #2199, surveyed April 2008/April 2009 - (DCSO rec Vol. 56 Pg 21928)

-----  
The closing cor. of secs. 4 & 5 only, established by Brooks and Jelley in 1963-65; monumented with an iron post, 2½" dia., firmly set, projecting 5" above ground, with a brass cap (properly) mkd.  
from which the BTs mkd. by Brooks and Jelley in 1963-65  
A fir, 37" dia., bears S.23½°E., 109.2 ft., with a healed blaze. (Record, S.21¾°E., 114.2 ft.)  
A fir, 16" dia., bears S.49°W., 55.6 ft., with a healed blaze. (Record, S.47½°W., 58.7 ft.)  
From this corner, the original closing corner of secs. 4 and 5, bears N.0°28'E., 9.2 ft. monumented with the remains of the original cor. tree, a decayed fir stump, size indeterminate, from which the remains of an original BT  
A decayed stump, size indeterminate, bears S.18½°E., 52.1 ft., no marks visible.  
and a bearing tree mkd. by Price and Rigby in 1945  
A fir, 42" dia., bears S.50°W., 35.0 ft., no marks visible.