

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 32 & 33

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 865)

Set post 4" dia., 4 ft. long in ground for 1/4 sec. cor. marked 1/4 S on W face, raised mound of stone alongside.
No witness trees near.

BLM dependent resurvey by Norman D. Price, Cadastral Eng. & Geo. F. Rigby, Assoc. Cadastral Eng., under group #282, surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11402)

Proportional measurement
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor., with brass cap marked: 1/4
S 32|S 33
1945 from which
A Fir, 30" dia., bears N.2 1/2°E., 204 lks., mkd: 1/4 S33 BT.
A Fir, 30" dia., bears N.40 1/2°W., 171 lks., mkd: 1/4 S32 BT.

Gary Smithers - Feb. 2004 - C.S. File 65/49-22

Found - 1945 Brass Cap on Iron Pipe firmly set. We Set a 6 foot galvanized steel fence post alongside with top painted red.
Old Bearing Trees Taken in 1945 by GLO:
30" rotted D.Fir, N.40 1/2°W., 171 links, no marks, no tag.
The other record tree is gone.
New BTs- 9" D.Fir, N.71°W., 5.8 ft to spike set side center, scribed "T21R8 1/4 S32BT"with aluminum tag.
13" D.Fir, S.49°W., 16.7 ft to spike set side center, scribed "T21R8 1/4 S32BT"with aluminum tag
13" D.Fir, S.70°E., 33.5 ft to spike set side center, scribed "T21R8 1/4 S33BT"with aluminum tag
16" D.Fir, N.50°E, 13.6 ft to spike set side center, scribed "T21R8 1/4 S33BT"with aluminum tag.