

Alias	Description
Alias	Description
Alias	Description
Alias	Description

9" D.Fir bears N.65°E., 3.8' blazed, scribed "T21S R8W S28 BT"
13" D.Fir bears S.30°E., 9.3' blazed, scribed "T21S R8W S33 BT"
12" D.Fir bears S.68°W., 8.7' blazed, scribed "T21S R8W S32 BT"
10" D.Fir bears N.88°W., 19.9' blazed, scribed "T21S R8W S29 BT"
2½" GLO brass cap set as witness corner dated 1945 bears N.0°35'00"E., 85.80'

Note- All BTs established during this survey have red painted faces, red painted band around the tree & yellow BT tag. There is a 5½' galvanized steel post adjacent to all corners.

Gary Smithers - Feb. 2004 - C.S. File 65/49-19

Found - 1945 Witness Comer, Brass Cap on Iron Pipe firmly set. We Set a 6 foot galvanized steel fence post alongside with top painted red. This corner is N.0°35'E., 1.30 chains from a 2" aluminum cap established at the true Section Comer in 2001 by Ward, properly marked and firmly set. We Set a 6 foot galvanized steel fence post alongside with top painted red.

Old Bearing Trees Taken in 1945 to Witness Corner by GLO
44" rotted Fir Stump, N.1°45'E., 165 links From WC, no marks, no tag.
44" rotted Fir Stump, S.31°E., 106 links From WC, no marks, no tag.
28" rotted Fir Stump, S.39°W., 70 links From WC, no marks, no tag.
44" rotted Fir Stump, N.0°45'W., 271 links From WC, no marks, no tag.

Bearing trees Taken in 2001 to True Corner Monument:
9" D. Fir, N 65°E., 3.8 feet to spike side center, with visible scribe and aluminum tag
13" D. Fir, S.30°E., 9.3 feet to spike side center, with visible scribe and aluminum tag.
12" D. Fir, S.68°W., 8.7 feet to spike side center, with visible scribe and aluminum tag.
10" D. Fir, N.80°W. (rec. N.88°W.), 19.9 feet to spike side center, with visible scribe and aluminum tag.