

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 29

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

<p>GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 866)</p> <p>-----</p> <p>Set post 4" dia., 4 ft. long on mound of stone 18" high 3½ ft. sq. at base for ¼ sec. cor. marked ¼ S on W face.</p>
<p>BLM dependent resurvey by Norman D. Price, Cadastral Eng. & Geo. F. Rigby, Assoc. Cadastral Eng., under group #282, surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11404)</p> <p>-----</p> <p>Proportional measurement Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec. cor., with brass cap marked: ¼ S 29 S 28 1945 from which A Fir, 52" dia., bears N.76°E., 128 lks., mkd: ¼ S28 BT. A dead Fir, 60" dia. bears N.56°W. 172 lks. mkd: ¼ S29 BT.</p>
<p>Donald Bentz, LS 839 - For: International Paper Co. - Sept. 1989 - M 101-63</p> <p>-----</p> <p>Found - Brass cap mkd: ¼ S29 S28 New BTs- 13" D.Fir bears N.32°W., 8.4 ft. scribed. 13" D.Fir bears N.32°E., 11.8 ft. scribed. 6' alum. post with sign facing IP property with buried magnetic marker bears East 2 ft. 6' alum. post with sign facing IP property with buried magnetic marker bears N.0°31'12"E, 99.1 ft</p>
<p>Robert B. Ward - For: Roseburg Resources Co. - Nov. 2001 - M 139-25</p> <p>-----</p> <p>Found - 2½" GLO brass cap dated 1945 13" D.Fir bears N.31°W., 8.4' healed face. 10" D.Fir bears N.32°E., 11.8' healed face. New BTs- 12" D.Fir bears S.55°E., 2.9' blazed, scribed "¼ S28 BT" 13" D.Fir bears S.65°W., 20.9' blazed, scribed "¼ S29 BT"</p> <p>Note - All BTs established during this survey have red painted faces, red painted band around the tree & yellow BT tag. There is a 5½' galvanized steel post adjacent to all corners.</p>