

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 866)

Set post 6" dia., 4 ft. long with marked stone 18" in ground for corner to secs. 20, 21, 28 & 29, marked T21S, S 21 on NE, R8W, S 28 on SE, S 29 on SW, S 20 on NW face with 4 notches on E edge 2 on edge from which:

- Fir, 6" dia., bears N.15°E., 50 lks., mkd: T21S R8W S21 BT
- Fir, 4" dia., bears S.20°E., 45 lks., mkd: T21S R8W S28 BT
- Fir, 4" dia., bears S.20°W., 47 lks., mkd: T21S R8W S29 BT
- Fir, 4" dia., bears N.32°W., 15 lks., mkd: T21S R8W S20 BT

BLM dependent resurvey by Norman D. Price, Cadastral Eng. & Geo. F. Rigby, Assoc. Cadastral Eng., under group #282, surveyed May/Aug 1945 (DCSO records Vol. 27 Page(s) 11404-5)

Proportional measurement

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 20, 21, 28, & 29, with brass cap marked:

T21S R8W  
S 20 | S 21  
S 29 | S 28

1945

from which

- A dead Fir, 40" dia., bears N.58½°E., 42 lks., mkd: T21S R8W S21 BT.
- A Hemlock, 18" dia., bears S.4°E., 162 lks., mkd: T21S R8W S28 BT.
- A Fir, 32" dia., bears S.29°W., 263 lks., mkd: T21S R8W S29 BT.
- A dead Fir, 20" dia., bears N.14°W., 42 lks., mkd: T21S R8W S20 BT.

Raise a mound of stone 3 ft. base, 2 ft. high W. of corner.

The sec. cor. is located on a rocky saddle of ridge, divide between Smith River and Umpqua River, bears E & W.

Donald Bentz, LS 839 - For: International Paper Co. - Sept. 1989 - M 101-63

- Found - 1945 USGLO Brass cap
- New BTs- 8" D.Fir bears N.60°E., 57.5 ft. scribed.
  - 12" D.Fir bears N.20°W., 19.0 ft. scribed.
  - 8" Madrone bears S.83°W., 39.2 ft. scribed.
  - 32" D.Fir bears S.5°E., 106.4 ft. scribed.

continued next page

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Gary Smithers - 3/2001 - C.S. File 65/36-15

Found - 1945 brass cap on iron pipe firmly set on South edge of existing road with 6 ft. alum. post alongside with top painted red.

1945 BTs

40" dead Fir, N.58½°E., 42 lks. is gone due to existing road.

18" Hemlock, S.4°E., 162 lks. this is a 42" Fir with old & new healed faces (see M101-63). This was erroneously called a Hemlock by GLO.

32" D.Fir, S.29°W., 263 lks. is now 38" with healed face.

20" dead Fir, N.14°W., 42 lks. is now a burnt & rotting stump.

Raised mound of stone is gone.

1985 BTs

10" D.Fir, N.70°E. (rec. N.60°E.), 57.5 ft. with healed face & alum. tag.

15" D.Fir, N.5°W. (rec. N.20°W.), 19.0 ft. with scribe visible & alum. tag.

8" Madrone, S.83°W., 39.2 ft. with scribe visible & alum. tag.

42" D.Fir, S.5°E., 106.4 ft. with healed face alum. tag. This is the 1945 GLO BT (see above note).

New BT - 10" D.Fir, N.26°E., 26.0 ft. to spike set side center, scribed "T21S R8W S21 BT" with alum. tag.

Ronald Rice, Ward NW INC. - For: Roseburg Resources Co. - Oct. 2002 - M141-12

Found - 1945, 2½" GLO brass cap w/the following accessories  
11" D.Fir bears N.26°E., 26.0 ft (open face)

8" Madrone bears S.83°W., 39.2 ft (open face)

New BTs- 8" D.Fir bears S.88½°W, 40.5 ft ( scribed T21S R8W S29 BT)

7" D.Fir bears S.70¾°E, 59.2 ft (scribed T21S R8W S28 BT)