

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 21

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 867)

-----  
Set post 4" dia., 4 ft. long on mound of stone 18" high, 3½ ft. sq. at base for ¼ sec. cor. marked ¼ S on W face.  
No witness trees near.

BLM dependent resurvey by Norman D. Price, Cadastral Eng. & Geo. F. Rigby, Assoc. Cadastral Eng., under group #282, surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11406)

-----  
Proportional measurement  
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec. cor., with brass cap marked: ¼

S 20|S 21  
1945 from which

A dead Cedar, 28" dia., bears N.2°45'E., 95 lks., mkd: ¼ S21 BT.

A dead Cedar, 38" dia., bears S.35°W., 95 lks., mkd: ¼ S20 BT.

Ronald Rice, Ward NW INC. - For: Roseburg Resources Co. - Oct. 2002 - M141-12

-----  
The ¼ corner between sections 20 & 21 was not recovered. BTs were also searched for but not found. This corner was reset by proportionate measure as shown on map.

Set - 2½" aluminum cap on a 5/8" x 36" rebar mkd:

T21S R8W

¼

S20|S21

2002

54633LS

19" D.Fir bears N.35°E., 40.6 ft (scribed ¼ S21 BT)

13" D.Fir bears N.01°E., 14.4 ft (scribed ¼ S21 BT)

9" D.Fir bears S.75°W., 8.1 ft (scribed ¼ S20 BT)

14" D.Fir bears S.38°W, 25.8 ft (scribed ¼ S20 BT)