

PRIMARY CORNER DESCRIPTION Cor. Secs. 16, 17, 20, & 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 867-8)

Set post 6" dia., 4 ft. long on mound of rocks 18" high, 5 ft. sq. at base for corner to secs. 16, 17, 20 & 21, marked T21S, S 16 on NE, R8W, S 21 on SE, S 20 on SW, S 17 on NW face with 4 notches on E and 3 on S edges.
No witness trees near to mark.

BLM dependent resurvey by Norman D. Price, Cadastral Eng. & Geo. F. Rigby, Assoc. Cadastral Eng., under group #282, surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11407)

Proportional measurement

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 16, 17, 20, & 21,, with brass cap marked:

T21S R8W

S 17|S 16

S 20|S 21

1945

from which

A dead Cedar, 36" dia., bears N.34°E., 71 lks., mkd: T21S R8W S16 BT.

An Alder, 6" dia., bears S.24½°E., 148 lks., mkd: T21S R8W S21 BT.

A Maple, 24" dia., bears S.69½°W., 72 lks., mkd: T21S R8W S20 BT.

A dead Fir, 50" dia., bears N.9¼°W., 105 lks., mkd: T21S R8W S17 BT.

BLM remonumentation of certain orig. corner points by Wm. W. Glenn & James E. Jelley, Cadastral Surveyors, under group #s 350 & 635, surveyed April/May 1967 - (DCSO records C.S. File 65/27-1)

The cor. of secs. 16, 17, 20, & 21, monumented with an iron post, 2" dia., firmly set, projecting 6" above ground, with brass cap properly mkd, from which new BTS:

A Fir, 4" dia. bears N.54°E., 58 lks. mkd: T21S R8W S16 BT

A Fir, 4" dia., bears S.34½°W., 67 lks., mkd: T21S R8W S20 BT.

A Fir, 4" dia., bears N.55½°W., 132 lks., mkd: T21S R8W S17 BT.

continued next page

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Cor. Secs. 16, 17, 20, & 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ronald Rice, Ward NW INC. - For: Roseburg Resources Co. -
Oct. 2002 - M141-12

Found - 1945, 2½ GLO brass cap w/the following accessories;
25" D.Fir bears N.54°E., 38.3 ft (healed face)
28" D.Fir bears S.34½°W., 42.2 ft (healed face)
11" D.Fir bears N.55½°W., 87.1 ft (healed face)
New BT - 19" D.Fir bears N.65°W., 18.8 FT (scribed T21S R8W
S17 BT")

Ron Rice - 3/27/2006 - C.S. File 65/58-12

BTs found as reported, added a 5½" galvanized steel post is
set adjacent to corner. All BTs have red painted bands &
yellow BT tags.