TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 870)

Set post 4" dia., 4 ft. long with marked stone 12" in ground for ¼ sec. cor. marked ¼ S on W face from which:
Fir, 8" dia., bears N.2°E., 22 lks., mkd: ¼ S BT.
Fir, 6" dia., bears S.13°W., 21 lks., mkd: ¼ S BT.

BLM dependent resurvey by Norman D. Price, Cadastral Eng. & Geo. F. Rigby, Assoc. Cadastral Eng., under group #282, surveyed May/Aug 1945 (DCSO records Vol. 27 Page(s) 11410-1)

Proportional measurement
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec. cor., with brass cap marked: ¼
S 8|S 9
1945 from which
A Fir, 60" dia., bears S.9°E., 104 lks., mkd: ¼ S9 BT.
A Fir, 72" dia., bears S.52°W., 62 lks., mkd: ¼ S8 BT.

Ronald L. Rice, Ward NW - Aug. 15, 2008 - C.S. File 65/63-28

Found - 2½" brass cap (properly mkd) dated 1945 with the following accessories:
60" D.Fir stump bears S.9°E., 40.9' - rotted face (record S.9°E., 68.6')
72" D.Fir stump bears S.52°W., 68.6' - rotted face (record S.52°W., 40.9')
New BTs- 17" D.Fir bears S.60°W., 34.6' - blazed, scribed "¼ S8 BT"
13" D. fir bears N.7½°W., 4.3' - blazed, scribed "¼ S8 BT"
11" D. fir bears N.50½°E., 25.6' - blazed, scribed "¼ S9 BT"
11" D. fir bears S.45°E., 35.3' - blazed, scribed "¼ S9 BT"
Note - Corner has steel post adjacent to it. All BTs have red painted bands & yellow tags.
Compass decl. 17°E.