

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 872)

Set post 6" dia., 4 ft. long with marked stone 12" in ground for 1/4 sec. cor. marked 1/4 S on W face from which:

- Fir, 24" dia., bears S.24°W., 39 lks., mkd: 1/4 S BT.
- Fir, 24" dia., bears N.22°E., 26 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Norman D. Price, Cadastral Eng. & Geo. F. Rigby, Assoc. Cadastral Eng., under group #282, surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11413)

The 1/4 sec. cor., the locus of which is determined by reference to the record bearing & distance from each of the old BTs.

At corner point

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor. with brass cap marked:

1/4
S 5 | S 4
1945

- A Fir, 44" dia., bears N.22°E., 26 lks., marked on the bark BT 1/4 S. I re-blaze & re-mark this old BT 1/4 S4 BT.
- A burnt Fir stub, 40" dia., bears S.24°W., 29 lks., with no marks remaining on this OBT.
- A Maple, 12" dia., bears S.42°W., 66 lks., mkd: 1/4 S 5 BT. (New BT)

BLM remonumentation of certain orig. corner points by Wm. W. Glenn & James E. Jelley, Cadastral Surveyors, under group #s 350 & 635, surveyed April/May 1967 - (DCSO records C.S. File 65/27-1)

The 1/4 sec. cor. of secs. 4 & 5 monumented with an iron post, 1" dia., firmly set, projecting 6" above ground, with melted brass cap, no marks legible, from which the OBTs:

- A Fir, 60" dia., bears N.22°E., 29 lks., no marks remaining on burned out blaze. Rescribed 1/4 S4 BT on new blaze. (Rec. 26 lks.)
- A Fir stump, size indeterminate, bears S.31°W., 29 lks., no marks remaining on burned blaze. (Rec. S.24°W.)

and a BT mkd. in 1945

- A Maple, 18" dia., bears S.44°W., 66 lks., no marks remaining on burned blaze. (Rec. S.42°W.)

At corner point

Set a fiberglass post, 28" long, 2 1/2" dia., 26" in the ground, with brass cap marked:

1/4
S 5 | S 4
1945

continued next page

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which a new BT
A Maple, 5" dia., bears S.49°W., 69 lks., mkd: ¼ S5 BT.
Deposit the 1" iron post at base, & set a 6 ft. steel
fence post alongside the iron post.

Dependent resurvey by Edith M Forkner, Cadastral Surveyor,
under Group #2285, surveyed Aug. 2009/ Feb. 2010 (DCSO
records BLM plat 2011 & Vol. 56 Page(s) 22263-65)

The ¼ sec. cor. of secs. 4 & 5, remonumented by Price & Rigby
in 1945 and by Glenn, et al., in 1967; monumented with an
iron post (Record, fiberglass), 2½" dia., firmly set,
projecting 4" above ground, with a brass cap (properly) mkd.
from which the remains of an original BT
A fir snag, splitting, 73" dia., bears N.22°E., 19.1 ft.
with a healed blaze.
and new bearing trees
A fir. 17" dia., bears N.77½°E., 17.0 ft., mkd. ¼ S4 BT.
A fir, 16" dia., bears S.23½°W., 17.0 ft., mkd. ¼ S5 BT.
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail)
driven at the base right side-center.
A steel fence post is alongside the cor.
Corner is located W., 460 ft. from Big Creek Road. asphalt
surface, 15 ft. wide, bearing S.80°E. and S.70°W., and N.,
1045 ft. of same road. 20 ft. wide, bearing N.55°E. and
S.65°W., and N., 1140 ft. from Big Creek, 15 ft. wide, course
E, in bottom land 30 ft. wide.