

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 33

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 866)

-----  
Set post 4" dia., 4 ft. long on mound of stone 18" high 3½ ft. sq. at base for ¼ sec. cor. marked ¼ S on N face.

BLM dependent resurvey by Norman D. Price, Cadastral Eng. & Geo. F. Rigby, Assoc. Cadastral Eng., under group #282, surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11403)

-----  
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for witness cor. to the ¼ sec. cor., with brass cap mkd:

WC  
¼  $\frac{S\ 28}{S\ 33}$   
1945

from which

A Fir, 22" dia., bears N.81¼°W., 11 lks., mkd: WC ¼ S28 BT

A Fir, 26" dia., bears S.6°W., 47 lks., mkd: WC ¼ S33 BT.

(S.87°26'W., 0.86 chs.)

Proportionate point for ¼ sec. cor., on insecure ground on precipitous W. slope.

Robert B. Ward - For: Roseburg Resources Co. - Nov. 2001 - M 139-25

-----  
Found - 2½" GLO brass cap dated 1945  
22"x10" D.Fir staub bears N.71°W., 6.8' no visible marks. (Rec. N.81¼°W., 11 lks.)  
18"x10" D.Fir snag bears S.6°W., 31.0' visible axe work.

New - 10" D.Fir bears S.65°W., 9.8' blazed, scribed "X" at breast height "WC ¼ S33 BT" at base.  
10" D.Fir bears N.26°E., 21.5' blazed, scribed "X" at breast height "WC ¼ S28 BT" at base.  
13" D.Fir bears N.58°E., 20.5' blazed, scribed "X" at breast height "WC ¼ S28 BT" at base.  
12" D.Fir bears S.66°E., 11.0' blazed, scribed "X" at breast height "WC ¼ S33 BT" at base.  
1941 GLO rec. position for true ¼ corner is S.87°26'W., 0.86 ch. from WC.

Note - All BTs established during this survey have red painted faces, red painted band around the tree & yellow BT tag. There is a 5½' galvanized steel post adjacent to all corners.