TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 340400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 & 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 868)

Set post 4" dia., 4 ft. long with marked stone 12" in ground for ¼ sec. cor. marked ¼ S on N face from which:
Fir, 6" dia., bears N.29°E., 19 lks., mkd: ¼ S BT.
Fir, 4" dia., bears S.41°W., 20 lks., mkd: ¼ S BT.

BLM dependent resurvey by Norman D. Price, Cadastral Eng. & Geo. F. Rigby, Assoc. Cadastral Eng., under group #282, surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11407)

Proportional measurement
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec. cor., with brass cap marked: ¼ S 16 / S 21 / 1945 from which
A Fir, 44" dia., bears N.1½°W., 100 lks., mkd: ¼ S16 BT.
A Fir, 60" dia., bears S.37¼°W., 54 lks., mkd: ¼ S21 BT.

Ronald Rice, Ward NW INC. - For: Roseburg Resources Co. - Oct. 2002 - M141-12

Found - 1945, 2½" GLO brass cap w/the following accessories;
70" D.Fir bears N.1½°W., 66.0 ft
87. D.Fir bears S.37¼°W., 35.6 ft (healed face)
New BTs- 9" D.Fir bears S.65°W., 9.1 ft (scribed ¼ S21 BT)
12" D.Fir bears N.27°E., 12.0 ft (scribed ¼ S16 BT)