

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 869)

Set post 4" dia., 4 ft. long on mound of stone 18" high, 3½ ft. sq. at base for ¼ sec. cor. marked ¼ S on N face.
No witness trees near.

BLM dependent resurvey by Norman D. Price, Cadastral Eng. & Geo. F. Rigby, Assoc. Cadastral Eng., under group #282, surveyed May/Aug 1945 (DCSO records Vol. 27 Page(s) 11409-10)

Proportional measurement
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec. cor., with brass cap marked: ¼ $\frac{S \ 9}{S \ 16}$
1945 from which
A Hemlock, 36" dia., bears N.16°W., 106 lks., mkd: ¼ S9 BT.
A Hemlock, 50" dia., bears S.89°E., 40 lks., mkd: ¼ S16 BT.

BLM remonumentation of certain orig. corner points by Wm. W. Glenn & James E. Jelley, Cadastral Surveyors, under group #s 350 & 635, surveyed April/May 1967 - (DCSO records C.S. File 65/27-1)

The ¼ sec. cor. of secs. 9 & 16, monumented with an iron post, 1" dia., firmly set, projecting 6" above ground, with brass cap properly mkd, from which new BTs:
A burned Fir stump, 35" dia., bears N.2°E., 79 lks., mkd: ¼ S9 BT.
A burned Fir, 23" dia., bears S.45°W., 4½ lks., mkd: ¼ S16 BT.
Set 6 ft. steel fence post alongside the iron post.

Clyde Mulkins - for: I.P. Timberlands - 8/20/1995 - M122-77

Found - 1945 GLO 2½" Brass cap
1945 GLO W.Hem stump, with no marks, rec. 36", bears N.16°W. 106 lks. stump center indeterminate
1945 GLO W.Hem rotted stump, rec. 50", bears S.89°E., 40 lks., stump center indeterminate.
32" D.Fir rotted stump of unknown origin, bears North 51', visible scribed marks.
38" D.Fir of unknown origin (BLM TAG), bears S.50°W., 3.6', with healed face.
6' steel post beside corner

continued next page

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs- 10" D.Fir, bears N.7½°W., 27.4', scribed "¼ S 9 BT".
9" D.Fir, bears N.48°E., 31.2', scribed "¼ S 9 BT".
9" D.Fir, bears S.70°E., 35.8', scribed "¼ S 16 BT".
6' alum post beside corner with "Land Survey Monument" sign

Found OK by R. Rice, Oct. 2002 - M141-12