

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 340640

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2285, surveyed Aug. 2009/ Feb. 2010 (DCSO records BLM plat 2011 & Vol. 56 Page(s) 22263-65)

Point for the center ¼ sec. cor. of sec. 4, at intersection of the N. and S., and E. and W. center lines.
Set a stainless steel post. 28" long, 2½" dia., 24" in the ground, with brass cap mkd. T21S R8W
C¼ S 4
2009

from which
A fir, 14" dia., bears N.12°E., 12.7 ft., mkd. C¼ S4 BT.
A fir, 9" dia., bears S.28¾4°W., 8.0 ft., mkd. X at breast height BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.
Deposit a magnet in a white plastic case at the base of the stainless steel post.

Corner is located on nearly level ground in young timber with no undergrowth.
Latitude 43°46'10.48"N Longitude 123°39'03.20"W
(NAD 1983 (CORS 96))