

PRIMARY CORNER DESCRIPTION C C for Secs. 3 & 4 only, T22-8

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by W. H. Byars, under Contract #376 dated Jan. 22, 1881 (DCSO records Vol. 4 Page(s) 1603)

 Intersect North bdy. of Tp. 14.00 chs. West of the established cor. to secs. 33 and 34.

Set Fir post for the cor. to secs. 3 & 4, from which

A Fir 18" dia., bears S.20°E., 26 lks. dist.

A Fir 36" dia., bears S.70°W., 38 lks. dist.

GLO survey by Norman D. Price, Cadastral Engineer and Geo Rigby, Ass. Cadastral Engineer, under Group #282, surveyed May/Aug. 1945 (DCSO records, Vo. 27 Page 11378)

 A point on line from which the closing corner of secs. 3 and 4, determined by reference to the record measurement from each of the old bearing trees, bears South, 8 lks. dist.

At original point for closing corner,

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for closing cor. of secs. 3 and 4, with brass cap marked:

T 21 S R 8 W

S 33

S 4 | S 3

C C

T 22 S R 8 W

1945

from which

A Fir 32" dia., bears S.11¼°E., 26 lks. dist. mkd. on bark S4 T22S R8W. I reblaze and remark this old bearing tree T22S R8W S3 CC BT.

A Fir 52" dia., bears S.62°W., 38 lks. dist. with blaze healed. (Old BT)

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone & Wm. Stoffel, crew - Sept. 1963 - C.S. File 52/14-28

 Found - 1945 Brass cap in ground. Had obviously been recently reset, didn't fit bearing or distance to old BTs. Reset Brass Cap in proper position from 2 old BTs.

54" Fir S.62°W., 25.1 ft. portions of old scribing visible on badly burned face.

32" Fir stump, cut off approx. 8 ft. above ground, S.11¼°E., 17.2 ft. Cut open and find good scribing "W" on old face.

Reblaze and Scribe:

54" D.Fir S.62°W., 25.1 ft. mkd. "T22S R8W CC S4 CS BT".

(Cont. Next Page)

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 367100

PRIMARY CORNER DESCRIPTION C C for Secs. 3 and 4 only, T22-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

New BT - 48" Fir stump N.32°E., 78.2 ft. mkd. T22S R8W CC S4 CS BT.

No live trees available.

From corner as reset by Godfrey, the position where brass cap was found set bears N.38½°W., 14.5 ft.

Survey by Les Roberts - For: International Paper Co. - June 1986 - C.S. File 63/18-5(A) M 102-18

Found - 1945 GLO brass cap set firmly in the ground.
24" Fir stub S.07°E., 18.1 ft. (Rec. S.11¼°E., 17.2 ft.) 1881 BT. Scribe visible.
40" Fir S.64°W., 24.5 ft. (Rec. S.62°W., 25.1 ft.) 1881 BT. Scar visible.
6" Fir N.08°W., 29.5 ft. scar visible. No Record.
Set Metal fence post with survey attention sign wired to, beside cap. Painted all BTs red. Corner lies on NW slope approx. 150 ft. from dirt road.

Les Roberts - Feb. 10, 1997 - M 124-44 & C.S. 65/12-5 A&B

Mon. Fd. - 1945 GLO Iron pipe and Brass cap
Bt's Fd. - 48" Fir, S.62°W., 24' (scar vis.), 1881 B.T.
6" Fir, N.9°W., 29.1' (scar vis.), No record
10" Fir, S.51°E., 18.4' (scar vis.), no record
Mon. Set - 3/4" X 36" Alum. rod with 3" Alum cap at true point of intersection, 1945 BLM Brass cap bears S.1°28'15" W., 8.45'.

BLM dependent resurvey by Aaron M Graham, Cadastral Surveyor, under Group 1910, surveyed June/July 1999. (DCSO recs. Vol. 53 Page(s) 20495-7)

N.1°26'35"E., 2765.72 ft. bet. secs. 3 and 4.
The original closing corner of secs. 3 & 4, perpetuated by Godfrey, in 1963, utilized by Roberts, in 1986, and further utilized by Roberts, in 1997; monumented with an iron post, 2½" diam., firmly set, projecting 10" above the ground, with brass cap mkd.

T 21 S R 8 W
S 33
S 4 | S 3
T 22 S R 8 W
C C
1945

from which the remains of the original bearing trees
A fir snag, 22" diam., bears S.6¼°E., 18.2 ft., with scribe marks R8W visible on partially open blaze.
(Record, S. 11¼° E., 17.2 ft.) continued next page

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 367100

PRIMARY CORNER DESCRIPTION C C for Secs. 3 & 4 only, T22-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A fir, 54" diam., bears S.61°W., 24.4 ft., with a healed blaze. (Record, S.62°W., 25.1 ft.)
Add the marks AM to the brass cap and reset the monument 6" below the grounds surface.

2774.18 ft.

The true closing corner of secs. 3 & 4, established by Roberts, in 1997, and is accepted as the corner; monumented with a finned aluminum rod, 3/4" diam., firmly set, projecting 5" above the ground, with an aluminum cap mkd.

R L S 1039
T 21 S R 8 W
S 33
S 4 | S 3
C C
T 22 S R 8 W
1997

from which bearing trees mkd. by person(s) unknown

A fir, 11" diam., bears S.35½°E., 24.5 ft., with a healed blaze.

A fir, 7" diam., bears N.12 3/4°W., 20.9 ft., with a healed blaze.

From this point the cor. of secs. 33 & 34 only, on the S. bdy. of T21S., R8W., bears S.89°57'24"E., 847.92 ft.