TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 33 & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 856-7)

Oak, 6" dia., for ¼ sec. cor. marked ¼ S on W face from which:
Fir, 20" dia., bears S.45°W., 16 lks., mkd: ¼ S BT.
Fir, 20" dia., bears N.50°E., 24 lks., mkd: ¼ S BT.

BLM dependent resurvey by Norman D. Price, Cadastral Eng. & Geo. F. Rigby, Assoc. Cadastral Eng., under group # 282, surveyed May/Aug. 1945 (DCSO records Vol. 27 Page(s) 11394)

The ¼ sec. cor., a live Oak, 8" dia., with old blaze decayed. At point for cor., between the roots of old corner tree, which leans downhill, on solid sandstone,
Set an iron post, 1 ft. long, 1" dia., in a drill hole, 8" deep, with brass cap marked: ¼
S 33|S 34
1945 from which
A Fir, 30" dia., bears N.59½°E., 24 lks., with partial scribe marks on old bark blaze. I reblaze & remark this OBT ¼ S33 BT.
A Fir, 20" dia., bears S.38½°W., 16 lks., with blaze healed. I reblaze & remark this OBT ¼ S33 BT.

David Edwards - 5/7/1999 - C.S. File 65/23-9

Found - 1945 brass cap.
BTs & corner tree gone down the hill.
New BTs- 9" Fir scribed: ¼ S34 BT bears N.17°E., 16.2 ft
5" Fir scribed: ¼ S34 BT bears N.50°E., 11.7 ft
28" Fir scribed: ¼ S34 BT bears S.38°E., 22.5 ft
A Steel post bears North 15.45 ft.

Fd. BC, 3 BTs & steel post by Ron Rice, 7/20/2013 - C.S. File 65/80-1 & (C.S. File 65/81-11 Filed 4/24/2014)