

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor. Secs. 27, 28, 33, & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 857)

Maple, 5" dia., for cor. to secs. 27, 28, 33 & 34 mkd: T21S, S 27 on NE, R8W, S 34 on SE, S 33 on SW, S 28 on NW face with 3 notches on E and 1 notch on S edge from which:

- Fir, 4" dia., bears S.70°W., 29 lks., mkd: T21S R8W S33 BT
- Fir, 6" dia., bears S.60°E., 30 lks., mkd: T21S R8W S34 BT
- Cedar, 30" dia. bears N.70°E. 90 lks. mkd: T21S R8W S27 BT
- Cedar, 10" dia. bears N.40°W. 27 lks. mkd: T21S R8W S28 BT

BLM dependent resurvey by Norman D. Price, Cadastral Eng. & Geo. F. Rigby, Assoc. Cadastral Eng., under group #282, surveyed May/Aug. 1945 - (DCSO recs Vol. 27 Page(s) 11394-5)

N.0°32'E., 39.44 chs. (from ¼ cor. between secs. 33 & 34)
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for W.C. to the cor. of secs. 27, 28, 33, & 34, with brass cap mkd:

WC
T21S R8W
S 28|S 27
S 33|S 34
1945

from which

- A Cedar, 36" dia., bears N.26¼°E., 170 lks., mkd: WC T21S R8W S27 BT.
- A Fir, 36" dia., bears S.35°45'E., 150 lks., mkd: WC T21S R8W S34 BT.
- A Hemlock, 18" dia., bears S.62°W., 90 lks., mkd: WC T21S R8W S33 BT.
- A Fir, 40" dia., bears N.58½°W., 222 lks., mkd: WC T21S R8W S28 BT.

N.0°32'E., 39.54 chs. (from ¼ cor. between secs. 33 & 34)
The cor. of secs. 27, 28, 33, & 34, a maple, 22" dia., badly decayed, w/surface scar remaining on the E. side; from which:

- A Cedar stub, 40" dia., bears N.7°E., 83 lks., on which no marks remain. (OBT)
- A Hemlock, 26" dia., bears S.40°E., 30 lks., with partial scribe marks on decayed face of old blaze. (OBT)

David Edwards - 5/7/1999 - C.S. File 65/23-9

Witness monument to NW sec. cor. Sec. 34

- Found - 1945 GLO brass cap.
- 48" Cedar N.26¼°E., 170 lks. 1945
- 72" Fir N.58½°W., 222 lks.

- New BTs- 17" Hemlock scribed S34 WC BT, bears S.60°E. 17.94 ft
- 11" Fir scribed S33 WC BT, bears S.88°W., 15.13 ft.

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor. Secs. 27, 28, 33, & 34

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Found OK by R. Ward, Nov. 2001 - M139-25