

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 28

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 857-8)  
-----  
Set post 4" dia., 4 ft. long with marked stone 12" in ground for 1/4 sec. cor. marked 1/4 S on W face from which:  
Willow, 3" dia., bears N.80°E., 18 lks., mkd: 1/4 S BT.  
Fir, 70" dia., bears S.30°W., 40 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Norman D. Price, Cadastral Eng. & Geo. F. Rigby, Assoc. Cadastral Eng., under group #282, surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11395)  
-----  
The 1/4 sec. cor., the locus of which is determined at the rec. bearing & dist. from the old SW BT.  
At the corner point  
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap marked: 1/4  
S 28 | S 27  
1945 from which  
A Fir, 74" dia., bears S.30°W., 40 lks., with only axe marks remaining on charred face of old blaze. I re-blaze & re-mark this old BT 1/4 S28 BT.  
A Fir, 42" dia., bears S.27 1/2°E., 159 lks., mkd: 1/4 S27 BT. (new BT)  
The 1/4 sec. cor. is located at edge of green timber, bears SE & SW.

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #1000, surveyed May 1999/April 2000 - (DCSO rec. Vol. 54 Page(s) 20744)  
-----  
The 1/4 sec. cor. of secs. 27 & 28, monumented with an iron post, 1" dia., firmly set, projecting 12" above the ground, with brass cap (properly) mkd.  
from which the remains of an original bearing tree  
A fir, 79" dia., bears S.19°W., 31.7 ft., with a healed blaze. (Record, S.30°W., 26.4 ft.)  
and new bearing trees  
A fir, 12" dia., bears N.49 3/4°E., 23.4 ft., mkd. 1/4 S27 BT.  
A fir, 19" dia., bears N.28 3/4°W., 66.6 ft., mkd. 1/4 S28 BT.