

PRIMARY CORNER DESCRIPTION Cor. Secs. 21, 22, 27, & 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 858)

Fir, 10" dia., for cor. to secs. 21, 22, 27, & 28, marked T21S, S 22 on NE, R8W, S 27 on SE, S 28 on SW, S 21 on NW face with three notches on E and 2 on S edge from which:

- Fir, 25" dia., bears N.37°E., 26 lks., mkd: T21S R8W S22 BT.
- Fir, 30" dia., bears N.10°W., 26 lks., mkd: T21S R8W S21 BT.
- Fir, 10" dia., bears S.27°W., 18 lks., mkd: T21S R8W S28 BT.
- Fir, 10" dia., bears S.45°E., 39 lks., mkd: T21S R8W S27 BT.

BLM dependent resurvey by Norman D. Price, Cadastral Eng. & Geo. F. Rigby, Assoc. Cadastral Eng., under group #282, surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11396)

The cor. of secs. 21, 22, 27, & 28, determined at the record bearing & distances from all of the OBTs.

At point for corner,
Set an iron post, 3' long, 2" dia., 28" in the ground, for cor. of secs. 21, 22, 27, & 28, with brass cap marked:

T21S R8W
S 21|S 22
 S 28|S 27
 1945

from which

- A dead Fir, 32" dia., bears N.37°E., 26 lks., with blaze healed. (OBT)
- A Hemlock stub, 14" bears S.45°E., 39 lks., with blaze healed. (OBT)
- A dead Fir, 12" dia., bears S.27°W., 18 lks., with blaze healed. (OBT)
- A dead Fir, 40" dia., bears N.10°W., 26 lks., on which I uncover the scribe marks BT T21S R8W S21 (OBT)
- A dead Fir, 40" dia., S.13°45'W., 135 lks., mkd: T21S R8W S28 BT (New BT)

Raise a mound of stone, 2 ft. base, 1½ ft. high, W of cor.

Ronald L. Rice, Ward NW Inc. - Ben Pastor - 10/25/2002 - C.S. File 65/44-24

Found - 2½" GLO brass cap (properly mkd.) with the following 32"x4' Fir stump bears N.37°E., 26 lks. (OBT) no marks.

40" Fir snag bears N.10°W., 26 lks., (OBT) no marks.

continued next page

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Cor. Secs. 21, 22, 27, & 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

40"x3' Fir stump bears S.13°45'W., 135 lks, no marks
Visible raised mound of stone, West of corner.
New Accessories (set by BLM) -
11" D.Fir bears S.45°E., 8.0 ft., open face.
12" D.Fir bears S.51¾°W., 22.0 ft., open face.
18" D.Fir bears N.37¾°W., 40.2 ft., open face.
18" D.Fir bears N.19¾°E., 27.2 ft., open face.

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor
under Group #1000, surveyed May 1999/April 2000 - (DCSO rec.
Vol. 54 Page(s) 20744)

The cor. of secs. 21, 22, 27, and 28, monumented with an iron
post, 2" dia., firmly set, projecting 6" above the ground,
with brass cap (properly) mkd.
from which the remains of original bearing trees
A fir stump, 32" dia., bears N.37°E., 17.2 ft., no marks
visible.
A fir snag, 38" dia., bears N.6½°W., 17.2 ft., no marks
visible. (Record, N.10°W.)
and the remains of a bearing tree mkd. by Price and Rigby
A fir stump, 40" dia., bears S.13¾°W., 89.1 ft., no marks
visible.
and new bearing trees
A fir, 16" dia., bears N.19¾°E., 27.2 ft., mkd. T21S R8W
S22 BT.
A fir, 11" dia. bears S.45°E. 8.0 ft. mkd. T21S R8W S27 BT
A fir, 11" dia., bears S.57¾°W., 22.0 ft., mkd. T21S R8W
S28 BT.
A fir, 16" dia., bears N.37¾°W., 40.2 ft., mkd. T21S R8W
S21 BT.