

PRIMARY CORNER DESCRIPTION Cor. Secs. 15, 16, 21, & 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 860)

Hemlock, 18" dia., for corner to secs. 15, 16, 21 & 22, marked T21S, S15 on NE, R8W, S22 on SE, S21 on SW, S16 on NW face with 3 notches on E & S edges from which:

Hemlock, 18" dia., bears N.62°E., 50 lks., mkd: T21S R8W S15 BT.

Hemlock, 18" dia., bears N.55°W., 37 lks., mkd: T21S R8W S16 BT.

Fir, 50" dia., bears S.83°E., 25 lks., mkd: T21S R8W S22 BT.

Fir, 50" dia., bears S.20°W., 40 lks., mkd: T21S R8W S21 BT.

BLM dependent resurvey by Norman D. Price, Cadastral Eng. & Geo. F. Rigby, Assoc. Cadastral Eng., under group #282, surveyed May/Aug. 1945 - (DCSO rec. Vol. 27 Page(s) 11397-8)

The cor. of secs. 15, 16, 21, & 22, a Hemlock stub, 36" dia., with surface scars on NE., SE., SW., & NW. sides; from which the OBTs

A Hemlock stub, 18" dia., bears N.42½E, 50 lks., with axe marks remaining on charred blaze.

A Fir stub, 40" dia., bears S.83°E., 25 lks., on which no marks remain.

A dead Fir, 50" dia., bears S.20°W., 40 lks., with partial scribe marks visible on previously opened old blaze.

A Hemlock stub, 12" dia., N.10°W., 37 lks., on which only axe marks remain.

N.0°50'E., 0.10 chs.

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for witness cor. to the cor. of secs. 15, 16, 21, & 22, with brass cap marked:

WC

T21S	R8W	
<u>S 16</u>	<u>S 15</u>	
S 21	S 22	from which

A dead Fir, 50" dia., bears N.10¼°E., 101 lks., mkd: WC T21S R8W S15 BT.

A dead Cedar, 36" dia., bears S.33¼°E., 91 lks., mkd: WC T21S R8W S22 BT.

A dead Fir, 50" dia., bears S.15°45'W., 53 lks., mkd: WC T21S R8W S21 BT. This is one of the OBTs which I re-blaze and re-mark.

A dead Fir, 46" dia., bears N.30¼°W., 76 lks., mkd: WC T21S R8W S16 BT.

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 15, 16, 21, & 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Marvin J. Lytle, Palmer Norseth, Thomas A. Tillman, Raymond Bicknell, Joseph S. Gawron, & Hans W. Thielsen, Cadastral Engineers, under Group #304, Surveyed Aug. 1952 - Oct. 1954 - (DCSO recs. Vol. 30 Page(s) 12577-8)

The corner of secs. 15, 16, 21, & 22, described by Price in the field notes of the dependent resurvey of the W. half of T21S R8W in 1945, as a hemlock stump, has been destroyed by fire, & only the remains of the roots are found.

At the corner point

Set an iron post, 3' long, 2" dia., 28" in the ground, with brass cap marked:

T21S R8W
S 16|S 15
S 21|S 22
1954

from which

An iron post, 3 ft. long, 2" dia., set 28" in the ground, for a reference monument, bears S.38°E., 50 lks. with brass cap marked T21S R8W S22 RM 1954 and an arrow pointing to the corner.

An iron post, 3 ft. long, 2" dia., set 28" in the ground, for a reference monument, bears N.38°W., 50 lks. with brass cap marked T21S R8W S16 RM 1954 and an arrow pointing to the corner.

From the corner point, the witness cor. to the cor. of secs. 15, 16, 21, & 22, set by Price in 1945, bears N.0°50'E., 10 lks., monumented with an iron post, 2" dia., 20" above ground, firmly set, with properly marked brass cap, from which remains of the BTs mkd. by Price in 1945:

A sawed & burned Fir stump, 50" dia., bears N.10¼°E., 101 lks., with no marks remaining.

A stump hole, 36" dia., bears S.33¼°E., 91 lks.

A sawed & burned Fir stump, 48" dia., bears S.15°45'W., 53 lks., bearing a rusted metal tag.

A Fir snag, 40" dia., bears N.30¼°W., 76 lks., with no marks remaining.

The remains of the OBTs are gone.

Ronald Rice - For: Roseburg Resources Co. - 10/2002 - M141-12

Found - 1954, 2½" BLM brass cap w/the following accessories;
2" brass cap RM, 1954 bears S.38°E. 33.0 ft.
2" brass cap RM, 1954 bears N.38°W, 33.0 ft.
2" brass cap WC, 1945 bears N.0°50'E. 6.6 ft.

New BTs- 11" D.Fir bears S.26°W. 3.2' (scribed T21S R8W S21BT)
11" D.Fir bears N.74°E. 10.1' (scribed T21S R8W S15BT)

FD. Ok Gary Smither, 12/2005 - C.S. File 65/54-42