

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 861)

Set post 4" dia., 4 ft. long with marked stone 12" in ground for 1/4 sec. cor. marked 1/4 S on W face from which:

Hemlock, 5" dia., bears S.80°E., 6 lks., mkd: 1/4 S BT.

Hemlock, 5" dia., bears N.50°W., 9 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Norman D. Price, Cadastral Eng. & Geo. F. Rigby, Assoc. Cadastral Eng., under group #282, surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11398)

Proportional measurement

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor., with brass cap marked: 1/4

S 16|S 15

1945 from which

A dead Cedar, 38" dia., bears N.15 1/2°E., 161 lks., mkd: 1/4 S15 BT.

A dead Cedar, 14" dia. bears N.7°W., 76 lks. mkd: 1/4 S16 BT

Ronald Rice, Ward NW INC. - For: Roseburg Resources Co. - Oct. 2002 - M141-12

Found - 1945 2 1/2" GLO brass cap w/the following accessories;
Both original BT's either missing or rotted

New BTS- 18" D.Fir bears N.36°W, 14.3 FT (Scribed 1/4 S16 BT)

11" D.Fir bears N.10°E., 6.1 ft. (scribed 1/4 S15 BT)

18" D.Fir bears N.17°E., 5.7 ft. (scribed 1/4 S15 BT)

16" D.Fir bears S.52°W., 10.0 ft. (scribed 1/4 S16 BT)